



i3CAMERA PRO P1201





Endless compatibility


The plug & play connectivity allows endless compatibility with Microsoft Skype, Skype for Business, Teams, Zoom, Google Hangouts, Cisco Webex, Bleujeans, GoToMeeting, GoToWebinar and other video conferencing and recording applications that support USB cameras.

Never miss a thing

The i3CAMERA Pro 4K camera has a Wide Dynamic Range lens making it optimal for close-quarter meetings or hybrid classrooms. With the face recognition, built-in noise reduction and low light capacity, meetings and lessons are a breeze.

With a built-in 12 meter omnidirectional microphone, sound won't be an issue in larger meeting rooms and classrooms, brining exceptional clarity and making sure you can always get your point across.





Omnidirectional mic

With a built in microphone array, using an omnidirectional pickup working up to 12 meters, nobody will be out of reach again. Thanks to the noise suppressing algorithm voices will be crisp and clear.

Low light support

With the CMOS image sensor the camera is able to give you clean and clear images, even under low light conditions.





Wide dynamic range

With a wide angle up to 120°, you'll get everyone on the picture. A the same time, it supports EPTZ to remotely control the Pan, Tilt, and Zoom of the camera.

Face recognition

By enabling the face recognition, the camera will center on the faces in the room, to avoid distraction of other element.



PRODUCT SPECIFICATIONS Model name i3CAMERA PRO P1201 Article number 10010149 **CAMERA** Sensor 1/2.5", CMOS, Effective Pixel: 8.29M Scanning mode Progressive Lens mount M12 Lens Focus: f=2.8mm, FOV: 120° Minimal Illumination 0.05 Lux @ (F1.8, AGC ON) Shutter 1/30s ~ 1/10000s White Balance Auto, Manual Camera Bracket Optional Accessory Digital Noise Reduction 2D, 3D digital noise reduction Backlight compensation Supported Supported: Display-Top-Edge Clip, Table-Top Stand, Tripod Mount Screw Optional Accessory: VESA mounting bracket. **USB-FEATURES** Windows® 7, Windows 8.1, Windows 10 or higher, macOS™ 10.10 or higher, Google™ Chromebook™ Version 29.0.1547.70 or higher, Linux Operating system 2.4 GHz Intel® Core 2 Duo processor or higher GB RAM or more USB 2.0 port Color system/Compression H.264 / MJPEG / YUY2 / NV12 Video format UHD@30fps, 1080p@30fps/25fps, 720p@30fps/25fps, 960x540p@30fps/25fps, 640x360p@30fps/25fps

INPUT/OUTPUT INTERFACE

USB Video Communication Protocol UVC 1.1

USB interface 1x UXB 3.0: Type B

GENERAL SPECIFICATION

Input voltage	5V (USB power supply)
Power consumption	600mA (max)
Compatibility	Plug and play USB connectivity, Suitable for Skype for Business, Teams, Zoom® Meetings, Cisco Webex, Hangouts & other.
Warranty	2 years