

Part no:

38139

70m C6 HDBaseT HDMI & IR Extender with PoC



| DESCRIPTION

- Distributes HDMI resolutions up to 70m over Cat.6 network cable via HDBaseT technology
- Supports HDMI 10.2G resolutions up to 4K@30Hz 4:4:4
- CEC pass-through and bi-directional IR for simple control
- Supports PoC (Power over Cable), requiring a power supply connection from only one side of the installation
- 2 year warranty

The Lindy 70m Cat.6 HDMI & IR HDBaseT Extender with PoC is an end to end solution for extending HDMI signals over long distances via Cat.6 network cable.

The following distance and resolution combinations are possible when using high quality Cat.6 U/UTP or F/UTP cable:

70m: 1920x1080@60Hz 4:4:4 8bit

40m: 3840x2160@30Hz 4:2:0 8bit / 30Hz 4:4:4 8bit

Supporting resolutions up to 4K Ultra HD, video can be viewed in stunning clarity, providing a reliable solution for creating eye-catching digital signage in retail, immersive displays at events or engaging setups in larger conference rooms or lectures halls.

PoC (Power over Cable) functionality provides additional flexibility. This allows power to be supplied alongside data through Cat.6 network cable in a point to point connection between the transmitter and receiver, meaning only a single power supply is required at the transmitter unit. Ideal when power outlets are limited at the receiver end of the installation.

Featuring bi-directional IR ports at both sides of the setup, the source equipment can be easily controlled from the display side, and the display can also be controlled from the HDMI source side. Combined with CEC control, which allows commands from one main remote, this extension system allows for complete and simple control for the user.

In addition, the power supply is connected via a screw type DC jack, providing a more secure and reliable connection, perfect for professional installations where accidental disconnections could create a major issue.

HDBaset is a globally recognised standard for high quality distribution of AV content and other technologies, including power and control, over longer distances via low cost Cat.6 or above cable.

Specifications

- AV Interface: HDMI
- Interface Standard: HDMI 1.4
- Supported Bandwidth: 10.2 Gbps
- Maximum Distance: 70m (229.66ft)
- Maximum Resolution: 3840x2160@30Hz 4:4:4 8bit
- HDCP Support: Pass-through
- EDID Pass Through: Pass-through
- Supported Audio: Pass-through
- IR Support: 30-60kHz
- Transmission Protocol: HDBaseT
- Transmission Medium: 1 x Cat.5e/6
- Chipset: VS010
- Special Features: PoC (Power over Cat.6)

Connectors

- Transmitter Input: HDMI (Female), IR (Female)
- Transmitter Output: RJ45 (Female), IR Female)
- Receiver Input: RJ45 (Female), IR Female)
- Receiver Output: HDMI (Female), IR (Female)
- Power: 5.5/2.1mm DC socket

Physical Properties

- Dimensions WxDxH: 65x100x25mm (2.56x3.94x0.98in) per unit
- Housing Material: Metal
- Net Weight: 0.31kg (0.68lb) per unit
- Operating Temperature: 0°C - 40°C (32°F - 104°F)
- Storage Temperature: -20°C - 60°C (-4°F - 140°F)
- Humidity: 20-90% RH (non-condensing)
- Power Requirements: 24VDC 1A
- Colour: Black

Miscellaneous

- Packaging Type: Carton Box
- Packaging Dimensions: 193x191x69mm (7.6x7.52x2.72in)
- Gross Weight: 0.84kg (1.85lb)
- Warranty (Years): 2
- Certified: CE, UKCA, FCC, RoHS & REACH

Package Contents

- Transmitter unit
- Receiver unit
- 2 x IR emitter cable
- 2 x IR receiver cable
- Mounting kit
- Multi-Country Power Supply (EU, UK, US & AUS)
- Lindy manual