

Product datasheet

Specifications



Device monitoring and management, Network Management Cards, NMC3 for Easy UPS On-Line, secure remote UPS monitoring and management

AP9544

Overview

Presentation	The Network Management Card for Easy UPS On-Line (AP9544) enables secure remote monitoring and control of one Easy UPS Online through the easy-to-use web browser interface, via EcoStruxure™ IT Software or another SNMP-enabled system. A 12-month Secure NMC Subscription, that allows the customer to access future firmware updates, is included with the purchase of the card*. Upon expiration of the provided Secure NMC Subscription the purchase of a new Secure NMC Subscription is required to access future firmware updates. *The NMC Firmware must be V2.5 or later. Find the latest Firmware in the Software and Firmware section below.
--------------	---

Lead time	Usually in Stock
-----------	------------------

Main

Range of product	Network Management Cards
Range compatibility	Easy UPS On-Line Easy UPS 1 Ph On-Line
Product or component type	Device monitoring and management
Provided equipment	Micro-USB cable Installation manual
Number of input phases	1
Standards	CISPR 32 VCCI class A ICES-003 EN 55024 EN 61000-4-2 EN 61000-4-3 EN 61000-4-4 EN 61000-4-5 EN 61000-4-6 EN 61000-4-8 EN 61000-6-2 EN/IEC 62040-2

Physical

Net weight	0.05 kg
Width	5.2 cm
Height	4.4 cm
Depth	8.0 cm

Conformance

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product certifications	FCC Class A AS/NZS UK PSTI
------------------------	----------------------------------

Environmental

Storage Relative Humidity	0...95 %
Relative humidity	0...95 %
Ambient air temperature for storage	-15...65 °C
Ambient air temperature for operation	-5...45 °C
Storage altitude	0...15240 m
Operating altitude	0...10000 ft

Communications & Management

Communication network type	10/100/1000BASE-T
Authentication	Radius
Communication port protocol	HTTP over secure sockets Layer (HTTPS) SSH FTP HTTP SNMP DHCP BOOTP (Bootstrap Protocol) TCP/IP

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.600 cm
Package 1 Width	16.500 cm
Package 1 Length	23.000 cm
Package 1 Weight	284.000 g
Unit Type of Package 2	S06
Number of Units in Package 2	44
Package 2 Height	68.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	21.000 kg

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

🌱 Environmental footprint	
Total lifecycle Carbon footprint	69
Environmental Disclosure	Product Environmental Profile

Use Better

♻️ Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	F4c2965e-f80d-4830-8cd4-be926afb0f45
REACH Regulation	REACH Declaration

💡 Energy efficiency	
Energy Efficiency Optimized	Energy efficient product

Use Again

🔄 Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins