

Network Management Card, Network Management Cards, for Easy UPS 3 Series, 3-Phase, remotely monitor and manage the UPS

AP9547

Overview

Presentation

The Network Management Card for Easy UPS 3 Series (AP9547) enables secure remote monitoring and control of one Easy UPS 3S, Easy UPS 3S Pro, Easy UPS 3M or Easy UPS 3L through the easy-to-use web browser interface, via EcoStruxure™ IT Software or another SNMP-enabled system.

A 1-year Secure NMC System with IEC 62443-4-2 compliant NMC firmware updates is included with the purchase of the Network Management Card. After expiration of the 1-year included Secure NMC System, the purchase of an Advantage Plan (Plus, Prime, Ultra) or EcoCare membership with onsite maintenance visits for the UPS is required to get future NMC firmware updates.

Lead time Usually in Stock

Main

man .		
Range of product	Network Management Cards	
Range compatibility	Easy UPS 3S	
	Easy UPS 3M	
	Easy UPS 3L	
	Easy UPS 3S Pro	
	Galaxy PW 2nd generation	
Product or component type	Device monitoring and management	
Provided equipment	Micro-USB cable	
	Installation manual	
Number of input phases	3	
Standards	CISPR 32	
	VCCI class A	
	ICES-003	
	EN 55024	
	EN 61000-4-2	
	EN 61000-4-3	
	EN 61000-4-4	
	EN 61000-4-5	
	EN 61000-4-6	
	EN 61000-4-8	
	EN 61000-6-2	
	EN/IEC 62040-2	

Physical

Net weight	0.05 kg
Width	5.2 cm
Height	4.4 cm
Depth	8.0 cm

Conformance

Product certifications FCC Class A
AS/NZS

Environmental

Storage Relative Humidity	095 %
Relative humidity	095 %
Ambient air temperature for storage	-1565 °C
Ambient air temperature for operation	-1565 °C
Storage altitude	015240 m
Operating altitude	010000 ft

Communications & Management

Communication network type	10/100/1000BASE-T
Authentication	Radius
Authentication	Raulus
Communication port protocol	HTTP over secure sockets Layer (HTTPS) SSH FTP HTTP SNMP DHCP BOOTP (Bootstrap Protocol) TCP/IP

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.000 cm
Package 1 Width	16.500 cm
Package 1 Length	24.000 cm
Package 1 Weight	314.000 g
Unit Type of Package 2	P06
Number of Units in Package 2	44
Package 2 Height	55.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	17.000 kg

Contractual warranty

Warranty 24 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint		
Total lifecycle Carbon footprint	69	
Environmental Disclosure	Product Environmental Profile	

Use Better

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	F4c2965e-f80d-4830-8cd4-be926afb0f45
REACh Regulation	REACh Declaration
[⋄] Energy efficiency	
Energy Efficiency Optimized	Energy efficient product

Use Again

○ Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins