

Product datasheet

Specifications



Dry contact, Management Options, Dry Contact I/O Card, monitor external UPS environmental sensors, output relays, and input contacts

AP9614

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Range of product	Management Options and Cables
Provided equipment	User manual USB cable
Product or component type	Dry contact
Number of rack unit	0U
Cable length	0.159 m
Rated voltage	24 V
[In] rated current	0...200 mA

General

Power supply type	Self powered via SmartSlot
-------------------	----------------------------

Physical

Height	3.8 cm
Width	12.1 cm
Depth	12.8 cm
Net weight	0.20 kg
Mounting mode	Not rack-mountable

Conformance

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3 EN 61000-4-2 EN 61000-4-3 EN 61000-4-4 EN 61000-4-6 FCC part 15 class A FCC CFR 47 part 15 EN 61000-6-3 (2007) BS EN 61000-6-3 EN 55032 BS EN 55032 VCCI class A CISPR 32 EN/IEC 61000-3-2 AS/NZS CISPR 32 EN 61000-6-1 (2007) EN 55035 BS EN 55024 IEC 62040-2 BS EN 62040-2 EN 61326-2 BS EN 61326-2 BS EN 61000-4-2 BS EN 61000-4-3 BS EN 61000-4-4 EN 61000-4-5 BS EN 61000-4-5 BS EN 61000-4-6 EN 61000-4-8 BS EN 61000-4-8 EN 61000-4-11 BS EN 61000-4-11 BS EN 55035 EN 62040-2 ICES-003 class A EN 61000-6-3 BS EN 61000-3-2 BS EN 61000-3-3 AS/NZS EN 61000-3-2:2023 AS/NZS EN 61000-3-3:2023
-----------	--

Environmental

Ambient air temperature for operation	0...40 °C
Operating altitude	0...10000 ft 0...50000 ft
Ambient air temperature for storage	-15...65 °C
Storage altitude	0...15240 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.1 cm
Package 1 Width	16.5 cm
Package 1 Length	23.8 cm
Package 1 Weight	440 g

Contractual warranty

Warranty	24 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Total lifecycle Carbon footprint	270
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACH Regulation	REACH Declaration

Energy efficiency	
Energy Efficiency Optimized	Energy efficient product

Use Again

Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No

Image of product / Alternate images

Alternative



