

Dry contact, Management Options, Dry Contact I/O Accessory, additional dry contact input and relay outputs

AP9810

# Overview

Lead time Usually in Stock

# Main

Range of product	Management Options and Cables	
Provided equipment	Cat 5 Ethernet cable User manual	
Product or component type	Dry contact	

# Complementary

Max current draw	40 mA
Input voltage	24 V
Output voltage	12 V at 25 mA DC

#### **General**

Power supply type Self powered via UPS interface port

# **Physical**

Net weight	0.14 kg
Width	25.4 cm
Height	3.3 cm
Depth	4.46 cm
Mounting preference	No preference

### Conformance

Standards	EN 61000-4-2	
	EN 61000-4-3	
	EN 61000-4-4	
	EN 61000-4-6	

# **Environmental**

Storage Relative Humidity	095 %
Relative humidity	095 %
Ambient air temperature for storage	-1565 °C
Ambient air temperature for operation	040 °C
Storage altitude	04572 m

Operating altitude	0 40000 5
Operating altitude	010000 ft
	050000 ft

# **Packing Units**

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.300 cm
Package 1 Width	25.400 cm
Package 1 Length	12.700 cm
Package 1 Weight	140.000 g
Unit Type of Package 2	PAM
Number of Units in Package 2	576
Package 2 Height	123.000 cm
Package 2 Width	120.000 cm
Package 2 Length	100.000 cm
Package 2 Weight	80.960 kg

# **Contractual warranty**

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Total lifecycle Carbon footprint	68
Environmental Disclosure	Product Environmental Profile

### **Use Better**

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACh Regulation	REACh Declaration
Halogen-free status	Product contains halogen above thresholds

### **Use Again**

○ Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins