DS SERIES

DS431LT4

43" 2500 nits High Brightness Digital Signage Display





SUNLIGHT VIEWABLE IMAGE



NARROW BEZEL



BUILT-IN MEDIA PLAYER



TRUECOLOR™ CALIBRATED



LOW POWER CONSUMPTION

Android is a trademark of Google LLC.

The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License.

FOR MORE INFOMATION



SPECIFICATION


MODEL


DS431LT4

Unit: mm [inch]

529.3 [20.84] (4 534.6 [21.05] (E


DIMENSIONS






					962.1 [37.88]
		_	8.7 [0	0.34]	8.7 [0.34]
0 [21.73]	8.7 [0.34]				940.9 [37.04] (Active Area) 944.7 [37.19] (Bezel Open)
			Active Area)	3ezel Open)	







MODEL		DOGOTETA
	LCD Panel Size	42.5"
	Native Resolution	1920 x 1080
	Brightness	2500 nits
	Color Depth	8 bits
	Contrast Ratio	4000:1
PANEL	Response Time (Typ.)	8 ms
	Viewing Angle	178° / 178°
	Light Lifetime (Typ.)	100,000 hrs
	Blackening Defect Free	Up to 110°C (230°F)
	Power Supply	Internal
DOI:/FD	Rated Voltage	100-240V ~ 50/60HZ
POWER	Power Consumption (Max.)	220 W
	Power Saving Mode	<1 W
	Bezel Width (T/B/L/R)	8.7 / 8.7 / 8.7 / 8.7 mm
	Cabinet Color	Black
	Monitor Dimension (LxHxD)	962.1 x 552.0 x 77.4 mm
MECHANICAL	Monitor Weight	18.1 kg
SPECS	Orientation	Portrait / Landscape
	VESA Mounting (LxH)	400 x 200 mm
	Carrying Handles	Yes
	Language	English
	Support SNMP (Up to V3.0)	Yes
	Image Retention Protection	Yes
FEATURE	Auto Orientation Sensor	Yes
	Ambient Light Sensor	Yes
	Power On/Off Scheduling	Yes
	OSD Menu Rotation	Yes
	HDMI 2.1 (HDCP 2.2)	x2 (1080p recommended)
INPUT	USB 2.0	x2
OUTPUT	Audio	x1
	RS-232	In x1
EXTERNAL	RJ-45	x1 (LAN)
CONTROL	ETK Port (Thermal)	x1
	ESK Port (IR, Ambient)	x1

ACCESSORY Quick Start Guide. Power Cord. Remote Control. Batteries. IR & Ambient Sensor CERTIFICATION CE/CB/FCC/ETL/RCM/RoHS/PSE/VCCI

Operating Temperature

Storage Temperature

Operating System Processor

Main Memory Interface

Clock Speed

Graphics

Storage

Multimedia


Humidity

INTERFACE

ENVIRONMENT

INTERNAL

PLAYER



0°~ 45° C

-20°~60° C

Android 11.0

1.5GHz DDR4, 2GB

Mali G52

Quad-core A53

10% ~ 80% RH Non-condensing

Internal: 8GB eMMC Flash

4K video decoders, 30/60fps H.264 /VP9 10bit, MPEG-1/2/4