# **DS SERIES**









SUSTAINED HIGH BRIGHTNESS



BUILT-IN MEDIA PLAYER



THERMAL MANAGEMENT



TRUECOLOR™ CALIBRATED

Android is a trademark of Google LLC.

The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License.

#### FOR MORE INFOMATION



#### **SPECIFICATION**

MODEL

### **DIMENSIONS**


Unit: mm [inch]


DS653LT5

65" LCD Panel Size 1920 x 1080 Native Resolution 4000 nits **Brightness** Color Depth 10 bits 4000:1 **PANEL** Contrast Ratio Response Time (Typ.) 8 ms (Typ.) 178° / 178° Viewing Angle 100 000 hrs Light Lifetime (Typ.) Up to 110°C (230°F) Blackening Defect Free Polarized Sunglasses Support Internal Power Supply 100-240V ~ 50/60HZ Rated Voltage 255 W / 550 W Power Consumption (Typ. /Max.) **POWER** Power Saving Mode < 100 W AC Out Bezel Width (T/B/L/R) 11.8 / 11.8 / 11.8 mm Cabinet Color Monitor Dimension (LxHxD) 1456.7 x 829.7 x 89.6 mm 39.1 kg MECHANICAL Monitor Weight Orientation Portrait / Landscape **SPECS** 400 x 400 mm, 600 x 400 mm VESA Mounting (LxH) Carrying Handles Yes English Language Support SNMP (Up to V3.0) Yes Image Retention Protection Auto Orientation Sensor Yes **FEATURE** Yes Ambient Light Sensor Power On/Off Scheduling OSD Menu Rotation HDMI 2.1 (HDCP 2.3) x2 (1080p recommended) DisplauPort **INPUT** USB 3.0 x1 Micro SD Slot x1 Audio x1 OUTPUT RS-232 In x1 **EXTERNAL** x2 (LAN) RJ-45 CONTROL ETK Port (Thermal) x1 x1 ESK Port (IR. Ambient) 0°~ 45° C Operating Temperature **ENVIRONMENT** -20°~60° C Storage Temperature Humidity 10% ~ 80% RH Non-condensing Android 8.0.0 Operating System Dual-core A73 and dual-core A53 Processor 1.5GHz Clock Speed DDR4, 2G Main Memory Interface INTERNAL Grapics Quad-core MaliG51 Internal: 16GB eMMC Flash **PLAYER** Storage External: Support Micro SD, Up to 32GB(exFAT) /128GB(FAT32) Multimedia 4K 10bits VP9/H265/H264 video decoders, up to 60fps 1080P other video decoders (VC-1, MPEG-1/2/4, VP8) Wireless Function **ACCESSORY** Quick Start Guide. Power Cord. Remote Control. Batteries. IR & Ambient Sensor

11.8 [0.46] 11.8 [







## **INTERFACE**

CERTIFICATION CE/CB/FCC/ETL/RoHS/PSE/VCCI

