


OF-270P-B2

27" PCAP Touch Monitor







Description

The new OF-270P-B2 27" full HD (1920 x 1080) P-CAP, 10-point touch, open-frame solution is designed to handle a wide variety of customer-specific touch applications. Equipped with a versatile I/O port selection, the new OF-270P-B2 monitor creates a convenient, hassle-free experience and is an exceptional choice for deployment in all sectors. The thin cable management system, bracket, and versatile design ensure the OF-270P-B2 monitor provides all capabilities necessary to create a unique solution for any customer application.

Featured Specifications

- Size: 27" TFT LCD
- Maximum Resolution: 1920 x 1080
- · Contrast Ratio: 4000:1
- Aspect Ratio: 16:9
- Brightness: 350 nits (no touch), 275 nits (P-CAP)
- View Angle: H: 178°, V: 178°
- Video Port: 1 x VGA, 1 x HDMI, 1 X DP
- · Warranty: 3 year

Specifications

Touch LCD Display	
Touch Screen	Projected Capacitive
Touch Points	10
Surface Treatment	AG (anti-glare)
Touch Screen Interface	USB-HID (Type B)
I/O Ports	
USB Port	1 x USB 2.0 (Type B) for Touch Interface (USB-HID)
Video Port	1 x VGA, 1 x HDMI, 1 X DP
Power Input	1 x DC In 12V Jack Power Input
Physical Properties	
Power Supply	50W (12V, 4.16A) External Power Adaptor
Speaker	-
Housing Color	Black
Construction	Glass, SECC Metal
Compliance	Front Panel IP54
Dimension (W x H x D) mm	651.0 x 395.0 x 39.6 mm
Net Weight (Kg)	8.2 Kg
Gross Weight (Kg)	9.9 Kg
Carton (W x H x D) mm	762.0 x 517.0 x 174.0 mm
VESA	100 x 100 mm
Physical Properties/ Ball Drop Test	IK08
Safety	
Certifications	CE, FCC, UL/cUL, RCM, RoHS
Environment	
Operating Temperature	-10°C ~ 50°C, 20% ~ 80% RH. Non-Condensing
Storage Temperature	-20°C ~ 60°C, 20% ~ 90% RH. Non-Condensing



www.MicroTouch.com | us.orders@microtouch.com

MicroTouch Interactive, Inc.