

SK-156P-A1

15.6" PCAP 3-in-1 Touch Monitor







Stand sold separately
Part #IS-000-A1

Description

The commercial-grade, SK-156P-Al, is a Full HD wide format convertible monitor perfect for a wide range of applications, embedded or exposed, that requires quality and reliability in high use environments. Versatile by design, this 15.6" wide monitor fits a variety of applications with the ability to withstand harsh conditions while retaining high performance levels. The IP65 rating coupled with an updated I/O selection for seamless integration and OSD controls built into the back housing create a user experience that is effortless and simplistic.

Featured Specifications

• Size: 15.6" TFT LCD

• Maximum Resolution: 1920 x 1080

· Contrast Ratio: 1000:1

· Aspect Ratio: 16:9

 Brightness: 450 nits (No Touch), 405 nits (P-CAP)

• View Angle: H: 178°, V: 178°

Video Port: 1 x VGA (DB15), 1 x HDMI, 1x DP

· Warranty: 3 year

Specifications

TOUCH LCD DISPLAY	Drainatad Canacitiva
Touch Screen	Projected Capacitive
Touch Points	10
Touch Screen Interface	USB-HID (Туре В)
I/O PORTS	
Serial Port	-
USB Port	1 x USB 2.0 (Type B) for Touch Interface
Video Port	1 x VGA (DB15), 1 x HDMI, 1x DP
Audio Port	-
Power Input	1 x 2.1 mm 12V DC Jack
PHYSICAL PROPERTIES	
Power Supply	Max. 60W (12V, 5A) External Power Adaptor
Speaker	-
Housing Color	Dark Gray
Construction	Glass, SECC metal, Plastic (ABS)
Compliance	Front Panel IP65 Compliant, Rear IPX1
Dimensions (W x H x D) mm	381.0 x 230.3 x 46.0 mm
Net Weight (kg)	3.5 kg
Gross Weight (kg)	5.8 kg
Carton (W x H x D) mm	455 x 315 x 150 mm
VESA	100 x 100 mm
Ball Drop	-
SAFETY	
Certifications	CE/FCC/CB/UL
ENVIRONMENT	
Operating Temperature	0°C ~ 40°C, 20% ~ 80% RH. Non-Condensing
Storage Temperature	-20°C ~ 60°C, 10% ~ 90% RH. Non-Condensing
OPTIONAL PERIPHERAL	
Industrial Stand	IS-000-A1 (Sold Separately)



www.MicroTouch.com | us.orders@microtouch.com

MicroTouch Interactive, Inc.