

NEC MultiSync® EA241WU LCD 24" Enterprise Display

Datasheet



NEC MultiSync® EA241WU Ultra-Narrow Bezel - best productivity with tailored ergonomics plus style and performance to complement the modern office

With full height adjustability from 0 to 150 mm and 170° swivel functionality, this 24" display enables the user to create an individually tailored workspace. Furthermore, built-in Low Blue Light technology filters out hazardous blue light emissions whilst Flicker-Free technology eliminates the effect of flickering thus ensuring the well-being of the user. Fulfilling the demand for future-ready performance and delivering all the quality and reliability commensurate with the NEC brand, the EA241WU is well positioned to maximise office productivity.

Performance AH-IPS screen technology with LED backlit panel delivers 300 cd/m² of brightness whilst keeping power consumption to a minimum.

Benefits

Ergonomic Office - full height adjustability (150 mm), swivel, tilt and pivot functionality ensures perfect individual workspace set-up.

Auto-Adjust Power Consumption - to minimize unnecessary power usage, the Human and Ambient Light Sensors adjust the display brightness according to user presence and room lighting conditions.

Protecting your eyes from strain and damage - Built-in Low Blue Light technology filters out hazardous blue light emissions whilst Flicker-Free technology eliminates any backlight flickering, thus

protecting your eyes against cataracts and macular degeneration without compromise to true-to-life display colour performance.

Best in form and function – future-ready design with 3-sided ultra-narrow bezel, available in black or white, complementing a fresh professional office interior.

Business Class Image Quality – Advanced High-Performance IPS (AH-IPS) panel provides the very best viewing angles as well as noticeably better colour reproduction.

Product Information

Product Name	NEC MultiSync® EA241WU
Product Group	LCD 24" Enterprise Display
Order Code	60004676 (BK), 60004677 (WH)

Display

Panel Technology	IPS TFT with W-LED backlight
Screen Size [inch/cm]	24 / 61
Screen Aspect Ratio	16:10
Pixel Pitch [mm]	0.270
Brightness (typ.) [cd/m²]	300
Contrast Ratio (typ.)	1000:1 (5000:1 dynamic contrast ratio)
Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Response Time (typ.) [ms]	5
Colours [Mio.]	16.77

Synchronisation Rate

Horizontal Frequency [kHz]	31.5 - 95
Vertical Frequency [Hz]	56 - 75

Resolution

Optimum Resolution	1920 x 1200 at 60 Hz			
Supported	1024 x 768; 1280 x 1024; 1280 x 960;	1366 x 768; 1400 x 1050; 1440 x 900;	1600 x 1200; 1680 x 1050; 1920 x 1200;	640 x 480; 800 x 600

Connectivity

Digital	1 x DisplayPort; 1 x DVI-D; 1 x HDMI; USB ver. 3.0 (3 down / 1 up)
Analog	1 x D-sub 15 pin

Electrical

Power Consumption on Mode [W]	15 (Eco Mode 2); 20 (typ.); 47 (max.)
Power Savings Mode [W]	0.3
Power Supply	internal power supply

Environmental Conditions

Operating Temperature [°C]	+5 to +35
----------------------------	-----------

Operating Humidity [%]	20 to 80
------------------------	----------

Ergonomics

Height adjustable stand [mm]	150
------------------------------	-----

Screen Tilt / Swivel [°]	-5 to +35; -170 to +170
--------------------------	-------------------------

Screen Rotate [°]	-90 to 90 (landscape to portrait mode)
-------------------	--

Mechanical

Bezel Width [mm]	0.8 (left/right/top)
------------------	----------------------

Dimensions (W x H x D) [mm]	With stand: 531.5 x 515.4 x 250
-----------------------------	---------------------------------

Weight [kg]	6.7
-------------	-----

VESA Mounting [mm]	100 x 100
--------------------	-----------

Additional Features

Special Characteristics	Ambient light sensor for optimized brightness levels; Carbon Footprint Meter; Carbon Savings Meter; ControlSync®; Customize Setting; DICOM preset; EcoModes; Human Sensor; LED Backlight Technology; NaViSet Administrator 2; Quick release Stand and Handle; sRGB Support; Touch Sensor Keys; USB ver. 3.0 (3 down / 1 up)
-------------------------	---

Colour Versions	Black Front Bezel, Black Back Cabinet; White Front Bezel, White Back Cabinet
-----------------	--

Cable Management	yes
------------------	-----

Kensington security slot	yes
--------------------------	-----

Plug and Play	VESA DDC2B; VESA DDCi
---------------	-----------------------

Audio	Headphone Jack; Integrated Speakers (1 W + 1 W)
-------	---

Adjust Functions	Audio Volume / Lock-Out; Auto Adjust; Brightness; Colour Temperature Control; Contrast; Control Sync; DV Mode; EcoMode; Fine Adjust (analog); Human Sensing; Intelligent Power Management; Language Select; LED Brightness; Monitor Information; NTAA (Non-Touch-Auto-Adjustment); On-Screen-Display (OSD) lock-out; One Touch Recovery; Power-Off Timer; sRGB
------------------	--

Shipping Content	Control Sync Cable; DisplayPort cable; Monitor; Power Cable; Setup Guide; USB Cable
------------------	---


Safety and Ergonomics	CE; EAC; EnergyStar 8.0; ErP; Flicker-free; ISO 9241-307 (pixel failure class I); Low Blue Light; PSB; RoHS; TCO 8.0; TÜV Ergonomics; TÜV GS; UL/C-UL or CSA; WEEE
Warranty	3 years warranty incl. backlight; optional 1st to 3rd year 24/7 usage warranty; optional 4th to 5th year warranty extension

Green Features


Energy Efficiency	Ambient light sensor; Energy consumption: 12 kWh/1000 h; Energy efficiency class: C; Human sensor; Intelligent power management
Ecological Materials	Downloadable manuals
Ecological Standards	Energy Star 8.0; TCO 8.0

* EnergyStar 8.0


* TCO 8.0



ErP




CE



TÜV GS



TÜV Ergonomics



RoHS



TCO 8.0

This document is © 2025 Sharp NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 28.10.2025