



Get ahead with the curved GC2781HSU-B1 featuring 144Hz refresh rate and 1ms response time

Immerse yourself in the curve and outpace the competition.

Standard flat panels can leave you feeling disconnected from the action, with motion blur and low contrast masking your targets. The G-MASTER GC2781HSU changes the game with a 1500R curved VA panel that matches the natural field of human vision, pulling you deeper into the world while offering a superior static contrast ratio for the black depth. Combined with a 144Hz refresh rate and 1ms MPRT, it eliminates ghosting and screen tearing, ensuring that every movement is fluid and every enemy is visible, even in the darkest corners of the map.

Available also with height adjustable stand : [G-Master GCB2784HSU-B1](#)



CURVED DESIGN 1500R

The 1500R curvature of the screen guarantees a realistic and comfortable viewing experience allowing you to really immerse yourself in the game.



VA PANEL TECHNOLOGY

Guaranteeing excellent contrast ratio making all the nuances between the light and dark colours clearly visible.

01 DISPLAY CHARACTERISTICS

Design	curved
Diagonal	27", 68,6cm
Panel	VA
Curved	1500R
Native resolution	1920 x 1080 @144Hz
Aspect ratio	16:9
Panel brightness	350 cd/m ²
Static contrast	4000:1
Advanced contrast	80M:1
Response time (MPRT)	1ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	16.7mln 8bit (sRGB: 99%; NTSC: 72%)
Horizontal Sync	30 - 160kHz
Viewable area W x H	597.9 x 336.3mm
Pixel pitch	0.311mm
Colour	black

02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x1 (ver. 1.4) DisplayPort x1 (ver. 1.2)
USB HUB	x2 (v. 2.0; 5V, 500mA)
Headphone connector	yes

03 FEATURES

Blue light reducer	yes
Flicker free	yes
Adaptive Sync support	FreeSync - 1920 x 1080 @48-144Hz
Control buttons	Power Indicator, Joystick: Power / Menu (Center), Up / Signal Select, Down, Left / i-Style Colour / Night Mode / Blue Light Reducer, Right / Volume
User controls	picture adjust (contrast, brightness, OD, HDR, FreeSync, ACR, Night Mode, Blue Light Reducer, Motion Blur Reduction, Gamma), input select, audio settings (volume, mute), store user settings (user modes), colour settings (6-axis, colour temperature, user preset, black tuner), image adjust (i-Style Colour, x-res technology, sharpness, HDMI range, direct drive mode, video mode adjust), language, setup menu (OSD horizontal position, OSD vertical position, OSD time, opening logo, power LED, DDC/CI control, USB charge), display information, reset
Speakers	2 x 2W

04 MECHANICAL

VESA mounting	100 x 100mm
Cable management system	yes

05 ACCESSORIES INCLUDED

Cables	power (1.85m), USB (1.5m), HDMI (1.85m)
Other	quick start guide, safety guide

06 POWER MANAGEMENT

Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	17W default, 0.5W stand by, 0.3W off mode

07 SUSTAINABILITY

Regulations	CB, CE, TÜV-Bauart, EAC, PSE, RoHS support, ErP, WEEE, VCCI, REACH, UKCA
Energy efficiency class (Regulation (EU) 2017/1369)	D

08 DIMENSIONS / WEIGHT

Product dimensions W x H x D	610,5 x 362,5 x 98,5mm
Box dimensions W x H x D	693 x 439 x 163mm
Weight (without box)	4kg
Weight (with box)	6,54kg
EAN code	4948570127528

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IYAMA CORPORATION. ALL RIGHTS RESERVED