


Crystal UHD Signage QMC

Product information sheet

FeaturesSpecsSupportCompare



*QMC series has earned an ENERGY STAR 8.0 certification from the Environmental Protection Agency for its energy efficiency and an Electronic Product Environmental Assessment Tool (EPEAT) certification in recognition of its eco-conscious efforts, such as its recycled plastic use. Also, QMC series is the first signage models to receive a product carbon footprint certification from TÜV Rheinland, a global testing body. *TÜV Rheinland was established in 1872 and headquartered in Cologne, Germany, TÜV Rheinland provides quality and safety certification services to multiple industries. The organization calculates its carbon footprint certification by evaluating the amount of greenhouse gases generated throughout the entire product lifecycle, ranging from production to disposal, based on internationally recognised standards.* The certification status of TÜV Rheinland Carbon Footprint may vary depending on the inch.

Specifications

Display

Diagonal Size	Panel Type
65"	VA
Resolution	Pixel Pitch (HxV)
3,840 x 2,160	0.372x0.372mm
Brightness (Typ)	Contrast Ratio
500 nit	4,000:1

Crystal UHD Signage QMC

Product information sheet

Features Specs Support Compare

Colour Gamut
72% (NTSC)

Glass Haze
25%

H-Scanning Frequency
30~81kHz

Maximum Pixel Frequency
594MHz

V-Scanning Frequency
48~75Hz

Contrast Ratio (Dynamic)
Mega

Operation Time Support
24/7

Connectivity

HDMI In
3

DP In
1

Version of HDMI
2

Version of DP
1.2

Version of HDCP
2.2

USB
2

IR In
Yes

Audio In
No

Audio Out
Stereo Mini Jack

RS232 In
Yes

RS232 Out
Yes

RJ45 In
Yes

WiFi
Yes

Bluetooth
Yes

Crystal UHD Signage QMC

Product information sheet

Features Specs Support Compare

AC 100~240V 50/60Hz 107 W

Power Consumption (Sleep Mode)
0.5 W

Dimension

Set Dimension (WxHxD)
1456.8 x 831.9 x 28.5 mm

Package Dimension (WxHxD)
1616 x 945 x 164 mm

Weight

Set Weight with Stand
21.5 kg

Package Weight
28.0 kg

Operation Conditions

Temperature
0°C~ 40°C

Humidity
10 ~ 80%, non-condensing

Mechanical Specification

VESA Mount
400 x 300 mm

Bezel Width
11.5mm (even)

Frame Material
Non-Glossy

Optional Feature

Mount
WMN-B50SC

Stand
STN-L6585C