

MPN: MO-TL-SM321A

SFP BX-D, 1.25Gb/s, 20Km Compatible with TP-Link TL-SM321A

Micro-Optics products provide seamless connectivity for all your current and future network hardware needs.

- ****100% TP-Link Compatible****



Specifications

Features	Brand compatibility	TP-Link
	Certification	MSA
	Compatible products	TP-Link TL-SM321A
	Easy to install	Yes
	Form factor	SFP
	Plug and Play	Yes
	RoHS compliance	Yes
Operational conditions	Operating relative humidity (H-H)	10 - 80 %
	Operating temperature (T-T)	0 - 70 °C
	Storage relative humidity (H-H)	10 - 85 %
	Storage temperature (T-T)	-40 - 85 °C
Packaging data	Number of products included	1 pc(s)
Performance	Cabling technology	1000BASE-BX10-D
	Fiber cable diameters supported (core/cladding)	9/125 μm
	Fiber optic connector	LC
	Maximum data transfer rate	1000 Mbit/s
	Maximum transfer distance	20000 m
	SFP transceiver standard	BX-D
	SFP transceiver type	Fiber optic
	Single-mode fiber (SMF) supported	Yes
Vendor information	Brand Name	Lanview
	Warranty	5 Year(s)

Other images

