

NEC MultiSync® E243F LCD 24" Enterprise Display

Datasheet





The ergonomic workspace communications hub

Break free of cable clutter and enjoy a single, all-encompassing communications hub via this workspace centrepiece, the MultiSync® E243F display. The 24" office workhorse featuring powerful 65W USB Type-C connectivity, manages video, audio, power and USB via a single cable. Supporting new open office standards in hot desking and 'bring your own device', the display is fully future-proofed with a high level of connectivity flexibility.

User wellbeing is high on the agenda with built-in Low Blue Light and Flicker-Free technology to protect the viewer's eyes without compromise to true-to-life display colour performance. Furthermore, advanced ergonomic adjustability ensures best individual workspace set-up to support sustained productivity.

Available in black or white to suit ergonomic and aesthetic preferences in an office or home environment, plus a minimal display footprint thanks to its ultra-narrow bezel and optional VESA thin client mount, the E243F perfectly complements the modern efficient workspace.

Benefits

Newest USB Type-C connectivity standard – optimize connectivity and declutter your desk; replace video, audio, power and USB cabling with just a single cable to connect your notebook/tablet PC with the display.

Future-proof flexibility – wide connectivity provides high-level flexibility with DP, HDMI, USB Type C, USB A and audio output.

Safeguarding user wellbeing – built-in Low Blue Light technology filters out hazardous blue light emissions whilst Flicker-Free technology eliminates any backlight flickering, thus protecting the users' eyes against cataracts and macular degeneration.

Ergonomic Office – full height adjustability (130 mm), swivel, tilt and pivot functionality ensures perfect individual workspace set-up.

Best in form and function – future-ready design with 3-sided ultra-narrow bezel, available in black or white, plus optional VESA mount plate for thin client devices.

Product Information

| Product Name | NEC MultiSync® E243F |
|---------------|------------------------------|
| Product Group | LCD 24" Enterprise Display |
| Order Code | 60005203 (BK), 60005204 (WH) |

Display

| Panel Technology | IPS TFT with W-LED backlight |
|---------------------------|---|
| Screen Size [inch/cm] | 24 / 60 |
| Screen Aspect Ratio | 16:9 |
| Pixel Pitch [mm] | 0.275 |
| Brightness (typ.) [cd/m²] | 250 |
| Contrast Ratio (typ.) | 1000:1 |
| Viewing Angle [°] | 178 horizontal / 178 vertical (typ. at contrast ratio 10:1) |
| Response Time (typ.) [ms] | 6 |
| Colours [Mio.] | 16.77 |
| | |

Synchronisation Rate

| Horizontal Frequency | 31.5 - 83 |
|-------------------------|-----------|
| [kHz] | |
| Vertical Frequency [Hz] | 50 - 75 |

Resolution

| Optimum Resolution | 1920 x 1080 at 60 |
|--------------------|-------------------|
| | 112 |

Connectivity

| Digital | 1 x DisplayPort; 1 x HDMI; 1 x USB Type C; USB ver. 3.1 (3 down / 1 up) |
|---------|---|
| Digital | TX DisplayFort, TX TIDMI, TX OSB Type C, OSB vel. 3.1 (3 down / T dp) |

Electrical

| Power Consumption on | 15 (Eco Mode 1); 15 (typ.); 20 (max.) |
|------------------------|---------------------------------------|
| Mode [W] | |
| Power Savings Mode [W] | 0.4 |
| Power Supply | integrated power supply |

Environmental Conditions

| Operating Temperature [°C] | +5 to +35 |
|----------------------------|-----------|
| Operating Humidity [%] | 20 to 80 |
| Storage Humidity [%] | 85 to 10 |
| Storage Temperature [°C] | 60 to -10 |

Ergonomics

| Height adjustable stand | 130 |
|-------------------------|--|
| [mm] | |
| Screen Tilt [°] | -5 to 25 |
| Screen Swivel [°] | 170 to -170 |
| Screen Rotate [°] | -90 to 90 (landscape to portrait mode) |

Mechanical

| Bezel Width [mm] | 1 (left and right); 1 (top) |
|------------------------|--|
| Dimensions (W x H x D) | 538.1 x 332.6 - 462.6 x 190 (Landscape mode) |
| [mm] | |
| Weight [kg] | With stand: 5 |
| VESA Mounting [mm] | 100 x 100 |

Additional Features

| Special Characteristics | Flicker Free; Low Blue Light; USB-C |
|--------------------------|---|
| Colour Versions | Black Front Bezel, Black Back Cabinet; White Front Bezel, White Back Cabinet |
| Cable Management | yes |
| Kensington security slot | yes |
| Plug and Play | VESA DDC2Bi |
| Audio | 1W + 1W (De-activateable); Headphone Jack |
| Adjust Functions | Auto Adjust; Brightness; Carbon Footprint Meter / Carbon Savings Meter; DV Mode; EcoMode; Language Select |
| Shipping Content | DisplayPort Cable; Power Cable; Setup Guide; USB-C Cable |
| Safety and Ergonomics | EnergyStar 8.0; Flicker-free; ISO 9241-307 (pixel failure class I); Low Blue Light; RoHS; TCO 8.0; TÜV Ergonomics; TÜV GS; WEEE |
| | |

Green Features

| Energy Efficiency | Carbon footprint meter / Carbon savings meter; ECOMode; Energy consumption: 18 kWh/1000 h; Energy efficiency class: E |
|----------------------|---|
| Ecological Standards | RoHS compliant; TCO 8.0 |

^{*} EnergyStar 8.0

^{*} TCO 8.0







TÜV GS





TCO 8.0

TÜV Ergonomics

This document is © 2025 Sharp NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 17.09.2025