SMARTMOUNT®
Articulating Wall Mount

FOR 50" TO 90"+ DISPLAYS*

Peerless-AV's SmartMount® Articulating Wall Mount series has been redesigned to accommodate larger displays, offering enhanced versatility and mounting options. The I-shaped adaptor centers displays, regardless of the VESA® pattern on the back, which eliminates hassle and extra costs when upgrading displays. The SA771PU extends displays up to 30.5" (774mm) or retracts to 3.0" (76mm) from the wall, granting increased swivel for large displays. Compatibility with In-Wall Box accessories (IB14X9-W, IB14X14-W) offers easier access to power or AV devices. Horizontal adjustment range is ±8" to center a display on a 16" stud-spaced wall. Meanwhile, the Hook-and-Hang™ feature produces simplified installation and One-Touch™ tilt technology provides an optimal viewing angle. Integrated cable management ensures a clean and professional installation.

Mounting Pattern
800 x 400mm (31.50" x 15.75")

Max Load
Wood, Concrete, Cinder, Breeze Block: 200lb (90.7kg)
25ga Steel Studs with 1/2" Drywall: 90lb (41kg)
25ga Steel Studs with 5/8" Drywall: 150lb (68kg)

- Universal mount accommodates 200 x 100 to 800 x 400mm VESA® mounting patterns

- ±90° of pivot allows for perfect display positioning

- Easy leveling ±5° after display installation

- Adjustable 15° forward tilt and 5° backward tilt for finding the optimal viewing angle

- Dual arms for a more secure installation

- Stylish wall plate covers create a finished look and are easy to install and remove

- I-shaped adaptor plate helps avoid blocking connections on back of display

- Includes all necessary wall and display attachment hardware

- Mounts to wood stud, concrete, cinder, breeze block or steel studs

HOOK-AND-HANG™ INSTALLATION
Simplifies the installation of the display on the tilt head of the wall mount

EXTENDS UP TO 30.5" (774mm)
Offers the perfect viewing angle

HORIZONTAL ADJUSTMENT
Easily shift the mount arms right or left up to ±8" (203mm) to center the display in a room, regardless of stud locations

OPEN ACCESS
Provides the maximum open area on the wall to allow flexible placement for outlets and/or in-wall boxes

LOCKING TILT
Lock the display at any angle with the ratcheting handle

VESA® PATTERN FLEXIBILITY
Adaptor plate can be raised or lowered to accommodate different VESA® patterns at the top, center, or bottom of the display for a perfect fit

INTEGRATED CABLE MANAGEMENT
Protects, contains and conceals cables for a clean, professional installation

Retracts to hold display
3.0" (76mm) from the wall

RoHS COMPLIANT

TAA COMPLIANT

Please visit peerless-av.com/en-us/patents for patent information.

*This display size range is simply a guideline for product selection. Displays larger than the screen size range may still be compatible as long as they fall within the VESA® pattern and max weight of the Peerless-AV® product.

Model Numbers

SA771PU	SmartMount® Articulating Wall Mount for 50" to 90"+ Displays

Product Specifications

	DIMENSIONS (W x H x D)	PRODUCT WEIGHT	LOAD CAPACITY	FINISH	AVAILABLE COLORS
SA771PU	32.36" x 21.06" x 3.00"-30.50" (822 x 535 x 76-774mm)	36.4lb (16.5kg)	Wood, Concrete, Cinder, Breeze Block: 200lb (90.7kg) 25ga Steel Studs with 1/2" Drywall: 90lb (41kg) 25ga Steel Studs with 5/8" Drywall: 150lb (68kg)	Scratch Resistant Fused Epoxy	Semi-Gloss Black

Package Specifications

	PACKAGE SIZE (W x H x D)	PACKAGE SHIP WEIGHT	PACKAGE UPC CODE	PACKAGE CONTENTS	UNITS IN PACKAGE
SA771PU	37.20" x 5.11" x 24.40" (945 x 130 x 620mm)	44.8lb (20.3kg)	735029266624	Wall Mount, Wall and Display Installation Hardware, Installation Instructions	1

Accessories

ACC415:	4-Pack Metal Stud Fastener Kit	IBA4-W:	Easy Mount Recessed Low Voltage Cable Plate
ACC925:	Security Fasteners for V200x200 to V800x400 Mounts	IBA5-W:	Recessed Low Voltage Media Plate with Duplex Surge Protector
ACC-IFB:	Interface Bracket for Various VESA® Adaptor Brackets	IB14X9-W:	14"x9" In-Wall Box
ACC-UCM:	Universal AV Component Mount	IB14X9-AC-W:	14"x9" In-Wall Box with Duplex Surge Protector
ACC-SB2:	Universal UC/VC Soundbar Mount	IB14X14-W:	14"x14" In-Wall Box
ACC-V900X:	Adaptor Accessory for 800 and 900mm Mounting Patterns	IB14X14-AC-W:	14"x14" In-Wall Box with Duplex Surge Protector
ACC-V1500X:	Adaptor Accessory for 1200 and 1500mm Mounting Patterns	PLP-UNM2:	Universal I-Shaped Adaptors for 43"-75" Displays
ACSBR1:	Universal Sound Bar Mounting Kit	PLP-UNL2:	Universal I-Shaped Adaptors for 50"-90" Displays
ACSBR2:	Universal Sound Bar Mount	WSP756:	24" Metal Stud Wall Plate

All dimensions = inch (mm)

TOP VIEW

SIDE VIEW COLLAPSED

WALL PLATE DETAIL

FRONT VIEW

SIDE VIEW EXTENDED +15°/-5° TILT

ADAPTOR DETAIL

Architect Specifications

The SmartMount® Articulating Wall Mount shall be a Peerless-AV model SA771PU and shall be located where indicated on the plans. Assembly and installation shall be done according to instructions provided by the manufacturer.

LIT-1400 rev.4