


ViewSonic® LCD DISPLAY TD2430

Key Features

- SuperClear® technology
- Frameless design
- HDMI, DisplayPort and VGA inputs
- 7H hardness screen
- Supports Windows® 7/8/10/11 and selected Android and Linux



Product Description

Laid flat or angled for customized comfort, this display delivers touchscreen versatility to the max. Offering fantastic flexibility for retail, education, or business settings, the ViewSonic® TD2430 is a 24" (23.6" viewable) Full HD display with 10-point multi-touch functionality. Delivering adjustable positioning, wide-angle viewing, and a durable design, the TD2430 has everything to accommodate your unique needs. Adding even more convenience, cross-compatibility with a wide range of operating systems includes Windows 10/11, and certain Android and Linux versions.* With a sleek edge-to-edge screen and frameless bezel, this intuitive touchscreen performs like your favorite tablet or smartphone to deliver a highly accurate, ultra-responsive touch experience ideal for interactivity in public environments, kiosk and wayfinding applications, classroom settings, and more. *Supports Windows 7/8/10/11, Linux 2.6.38 or later, and Android 4.0 or later.



Visit Us

www.viewsonic.com



DISPLAY		ERGONOMICS	
Display Size (in.):	24	Tilt (Forward/Back):	20° / 53°
Viewable Area (in.):	23.6	WEIGHT (IMPERIAL)	
Panel Type:	VA Technology	Net (lbs):	12.1
Resolution:	1920 x 1080	Net Without Stand (lbs):	12.1
Resolution Type:	FHD (Full HD)	Gross (lbs):	15.6
Static Contrast Ratio:	3,000:1 (typ)	WEIGHT (METRIC)	
Dynamic Contrast Ratio:	50M:1	Net (kg):	5.5
Light Source:	LED	Net Without Stand (kg):	5.5
Brightness:	200 cd/m² (typ)	Gross (kg):	7.1
Colors:	16.7M	DIMENSIONS (IMPERIAL) (WXHxD)	
Color Space Support:	8 bit (6 bit + Hi-FRC)	Packaging (in.):	25.3 x 17.1 x 5.5
Aspect Ratio:	16:9	Physical (in.):	22.6 x 13.9 x 1.9
Response Time (Typical GTG):	10ms	Physical Without Stand (in.):	22.6 x 13.9 x 1.9
Response Time (GTG w/OD):	10ms	DIMENSIONS (METRIC) (WXHxD)	
Response Time (Typical Tr+Tf):	25ms	Packaging (mm):	643 x 435 x 140
Viewing Angles:	178° horizontal, 178° vertical	Physical (mm):	573 x 353 x 47
Backlight Life (Hours):	40000 Hrs (Min)	Physical Without Stand (mm):	573 x 353 x 47
Curvature:	Flat	GENERAL	
Refresh Rate (Hz):	60	Regulations:	cTUVus, FCC-B, ICES003, Energy Star, CEC, MX-CoC, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, CCC, China RoHS, China Energy Label, CECP
Low Blue Light:	Software solution	PACKAGE CONTENTS:	TD2430 x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male-Male) x1, USB A/B Cable (v3.2; Male-Male) x1, Audio Cable (Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1
Flicker-Free:	Yes		
Color Gamut:	NTSC: 72% size (Typ) sRGB: 104% size (Typ)	Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Pixel Size:	0.272 mm (H) x 0.272 mm (V)	Warranty:	*Warranty offered may differ from market to market
Touch Screen:	Projected Capacitive, 10-point multi-touch	Power Management:	Energy Star standards
Surface Treatment:	Glossy, Hard Coating (7H)		
Cover Glass Thickness:	1.8mm		
COMPATIBILITY			
PC Resolution (max):	1920x1080		
Mac® Resolution (max):	1920x1080		
PC Operating System:	Windows 8/10/11 certified; macOS tested		
Mac® Resolution (min):	1920x1080		
CONNECTOR			
VGA:	1		
USB 3.2 Type A Down Stream:	2		
USB 3.2 Type B Up Stream:	1		
3.5mm Audio In:	1		
3.5mm Audio Out:	1		
HDMI 1.4:	1		
DisplayPort:	1		
Power in:	DC Socket (Center Positive)		
AUDIO			
Internal Speakers:	2Watts x2		
POWER			
Eco Mode (Conserve):	19W		
Eco Mode (optimized):	22W		
Consumption (typical):	25W		
Consumption (max):	28W		
Voltage:	AC 100-240V		
Stand-by:	0.5W		
Power Supply:	External Power Adaptor		
ADDITIONAL HARDWARE			
Kensington Lock Slot:	1		
CONTROLS			
Physical Controls:	1, 2, Up, Down, Power		
On Screen Display:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Setup Menu, Memory Recall		
OPERATING CONDITIONS			
Temperature:	32°F to 104°F (0°C to 40°C)		
Humidity (non-condensing):	20% to 90%		
WALL MOUNT			
VESA Compatible:	100 x 100 mm		
INPUT SIGNAL			
Frequency Horizontal:	RGB Analog: 24 ~ 82KHz, HDMI (v1.4): 15 ~ 82KHz, DisplayPort (v1.2): 15 ~ 82KHz		
Frequency Vertical:	RGB Analog: 50 ~ 75Hz, HDMI (v1.4): 24 ~ 75Hz, DisplayPort (v1.2): 24 ~ 75Hz		
VIDEO INPUT			
Digital Sync:	TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2)		
Analog Sync:	Separate/Composite/SOG - RGB Analog		