



LCD DISPLAY

VG3208-4K

Key Features

- SuperClear® VA panel with 4K UHD 3840 x 2160 resolution
- Height adjustable swivel stand with tilt function
- HDR10 Delivers Stellar Contrast and Color Accuracy
- Dual HDMI and DisplayPort inputs for flexible connectivity
- EnergyStar and EPEAT certified for sustainability



Product Description

The ViewSonic VG3208-4K is a 32" 4K monitor featuring dual HDMI and DisplayPort inputs for business and home use. The optimal screen performance and comfortable viewing are delivered through Eye ProTech technology, and various ViewMode presets. Expand your workspace and experience truly seamless, ergonomic multitasking on just one screen with a VESA-compatible mount at a low power consumption.

1. Menu Control Panel
2. Power In
3. HDMI*2
4. DisplayPort
5. Audio Out
6. VESA Compatible (Wall Mount 100x100mm)

Visit Uswww.viewsonic.com

DISPLAY

Display Size (in.):	32
Viewable Area (in.):	31.5
Panel Type:	VA Technology
Resolution:	3840 x 2160
Resolution Type:	UHD (Ultra HD)
Static Contrast Ratio:	3,000:1 (typ)
Dynamic Contrast Ratio:	50M:1
High Dynamic Range:	HDR10
Light Source:	LED
Brightness:	300 cd/m² (typ)
Colors:	16.7M
Color Space Support:	8 bit true
Aspect Ratio:	16:9
Response Time (Typical GTG):	4ms
Response Time (GTG w/OD):	4.34ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	60
Low Blue Light:	Software solution
Flicker-Free:	Yes
Color Gamut:	NTSC: 72% size (Typ) sRGB: 104% size (Typ)
Pixel Size:	0.182 mm (H) x 0.182 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

COMPATIBILITY

PC Resolution (max):	3840x2160
Mac® Resolution (max):	3840x2160
PC Operating System:	Windows 10/11 certified; macOS tested
Mac® Resolution (min):	3840x2160

CONNECTOR

3.5mm Audio Out:	1
HDMI 2.0 (with HDCP 2.2):	2
DisplayPort:	1
Power in:	DC Socket (Center Positive)

POWER

Eco Mode (Conserve):	25W
Eco Mode (optimized):	33W
Consumption (typical):	40W
Consumption (max):	42W
Voltage:	AC 100-240V
Stand-by:	0.5W
Power Supply:	External Power Adaptor

ADDITIONAL HARDWARE

Kensington Lock Slot:	1
Cable Organization:	Yes

CONTROLS

Physical Controls:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

WALL MOUNT

VESA Compatible:	100 x 100 mm
------------------	--------------

INPUT SIGNAL

Frequency Horizontal:	HDMI (v2.0): 15 ~ 140KHz, DisplayPort (v1.4): 24 ~ 140KHz
Frequency Vertical:	HDMI (v2.0): 24 ~ 60Hz, DisplayPort (v1.4): 48 ~ 60Hz

VIDEO INPUT

Digital Sync:	TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.4)
---------------	--

ERGONOMICS

Height Adjust (mm):	90
Swivel:	360°
Tilt (Forward/Back):	-4° / 20°

WEIGHT (IMPERIAL)

Net (lbs):	17.4
Net Without Stand (lbs):	12.1
Gross (lbs):	21.6

WEIGHT (METRIC)

Net (kg):	7.9
Net Without Stand (kg):	5.5
Gross (kg):	9.8

DIMENSIONS (IMPERIAL) (WXHxD)

Packaging (in.):	34.4 x 20.3 x 5.8
Physical (in.):	28.12 x 17.95~21.49 x 8.39
Physical Without Stand (in.):	28.12 x 16.83 x 2.33

DIMENSIONS (METRIC) (WXHxD)

Packaging (mm):	875 x 515 x 147
Physical (mm):	714.3 x 456~546 x 213
Physical Without Stand (mm):	714.3 x 427.48 x 59.22

GENERAL

Regulations:	Energy Star, EPEAT, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO
PACKAGE CONTENTS:	VG3208-4K x1, HDMI Cable (v2.0; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country)
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Warranty:	*Warranty offered may differ from market to market
Power Management:	Energy Star standards, EPEAT

