

Key **Features**

- Instant, secure access to your digital workspace using Windows Hello
- Crystal-clear video with a built-in Zoom® Certified 5MP pop-up camera with LED fill lights, microphone, and 5W speakers
- 21:9 ultra-wide screen with UWQHD 3440 x 1440 resolution
- 1500R curved panel
- Integrated docking station with Ethernet, and delivers up to 100W charging via USB-C connection



Product **Description**

The VG3457CV is a 34" ultra-wide curved video conferencing monitor with UWQHD 3440 x 1440 resolution and Windows Hello compatibility. Its 21:9 aspect ratio and 1500R curvature provide an immersive viewing experience. The Zoom® Certified pop-up webcam, speakers, and microphone deliver exceptional audiovisual quality, and the pop-up webcam can discreetly hide away for privacy when not in use. With Windows Hello, it offers secure facial recognition for quick and convenient logins, eliminating the dependency on passwords. Equipped with up to 100W and 15W USB-C ports and Ethernet, the VG3457CV serves as a complete integrated docking station for charging, data transfer, and network connectivity, effectively reducing cable clutter. Available for free download from the ViewSonic Display Portal (Coming soon), the vDisplay Manager software for on-screen display controls and vSplit for multi-window screen splitting offers efficient multitasking and enhances various workflows. Its extensive ergonomic flexibility allows for tilt, swivel, and height adjustments, enabling you to work comfortably.

1. 01. Speakers 2. 02. Menu Control Panel

1. 03. LED Fill Lights

1, 03. LED Fill Lights 2, 04. IR Light 3. 05. SMP Webcam 4. 06. IR Sensor 5. 07. Microphone 6. 08. VESA Compatible(Wall Mount 100x100mm)

7. 09. Power In 8. 10. USB Type A 3.2 Downstream*2 9. 11. Ethernet (RJ45) 10. 12. USB Type C 11. 13. DisplayPort 12. 14. HDMI*2

13. 15. Audio Out 14. 16. USB Type C (Quick Charging) 15. 17. USB Type A 3.2 Downstream*2

Visit Us

www.viewsonic.com

| -15.52 VICWOOTII | O V COTO I OV OT OVVQIID 21.5 Cui ved vide |
|------------------------------|---|
| DISPLAY | |
| Display Size (in.): | 34 |
| Viewable Area (in.): | 34 |
| Panel Type: | VA Technology |
| Resolution: | 3440 x 1440 |
| Resolution Type: | UWQHD (UltraWide QHD) |
| Static Contrast Ratio: | 3,000:1 (typ) |
| Dynamic Contrast Ratio: | 80M:1 |
| Light Source: | LED |
| Brightness: | 350 cd/m² (typ) |
| Colours: | 1.078 |
| Colour Space Support: | 10 bit (8 bit + FRC) |
| Aspect Ratio: | 21:9 |
| Response Time (Typical GTG): | 5ms |
| Response Time (GTG w/OD): | 5ms |
| Viewing Angles: | 178° horizontal, 178° vertical |
| Backlight Life (Hours): | 30000 Hrs (Min) |
| Curvature: | 1500R |
| Refresh Rate (Hz): | 100 |
| Low Blue Light: | Hardware solution |
| Flicker-Free: | Yes |
| Colour Gamut: | NTSC: 85% size (Typ) sRGB: 120% size (Typ) |
| Pixel Size: | 0.232 mm (H) x 0.232 mm (V) |
| Surface Treatment: | Anti-Glare, Hard Coating (3H) |
| COMPATIBILITY | 3 (·) |
| PC Resolution (max): | 3440x1440 |
| Mac® Resolution (max): | 3440x1440 |
| PC Operating System: | Windows 10/11 certified; macOS tested |
| Mac® Resolution (min): | 3440x1440 |
| CONNECTOR | |
| USB 3.1 Type C - Downstream: | 1 (15W power charger) |
| USB 3.2 Type A Down Stream: | 4 |
| USB 3.2 Type C Up Stream; | 1 (100W power charger) |
| DisplayPort Alt mode : | |
| 3.5mm Audio Out: | 1 |
| HDMI 2.0: | 2 |
| DisplayPort: | 1 |
| Power in: | 3-pin Socket (IEC C14 / CEE22) |
| Ethernet LAN (RJ45): | 1 |
| AUDIO | |
| Internal Speakers: | 5Watts x2 |
| POWER | 25W |
| Eco Mode (Conserve): | |
| Eco Mode (optimised): | 30W |
| Consumption (typical): | 35W |
| Consumption (max): | 60W |
| Voltage: | AC 100-240V |
| Stand-by: | 0.5W |
| Power Supply: | Internal Power Supply |
| ADDITIONAL HARDWARE | |
| Kensington Lock Slot: | 1 |
| Webcam: | 5.0M pixel |
| Cable Organisation: | Yes |
| Microphone: | Yes |
| CONTROLS | |
| Physical Controls: | Key 1 (eye), Key 2, Key 3, Key 4, Key 5, Key 6 (power) Input Select, Conference Mode, ViewMode, Colour Adjust, |
| On Screen Display: | Manual Image Adjust, Setup Menu |
| OPERATING CONDITIONS | |
| Temperature: | 32°F to 104°F (0°C to 40°C) |
| Humidity (non-condensing): | 20% to 90% |
| WALL MOUNT | |
| VESA Compatible: | 100 x 100 mm |
| INPUT SIGNAL | |
| Frequency Horizontal: | 30 ~ 150KHz |
| Frequency Vertical: | 48 ~ 100Hz |
| VIDEO INPUT | |
| Digital Sync: | TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.2), Micro- Packet - Type C |
| | |

| ERGONOMICS | |
|-------------------------------|--|
| Height Adjust (mm): | 110 |
| Swivel: | 120° |
| Tilt (Forward/Back): | -5° / 40° |
| WEIGHT (IMPERIAL) | |
| Net (Ibs): | 20.9 |
| Net Without Stand (lbs): | 15.4 |
| Gross (lbs): | 34.2 |
| WEIGHT (METRIC) | |
| Net (kg): | 9.5 |
| Net Without Stand (kg): | 7 |
| Gross (kg): | 15.5 |
| DIMENSIONS (IMPERIAL) (W | XHXD) |
| Packaging (in.): | 39 x 19.5 x 9.4 |
| Physical (in.): | 31.81 x 16.68~21.01 x 9.3 |
| Physical Without Stand (in.): | 31.81 x 15.41 x 4.53 |
| DIMENSIONS (METRIC) (WX | HXD) |
| Packaging (mm): | 990 x 495 x 238 |
| Physical (mm): | 808 x 423.7~533.7 x 236.2 |
| Physical Without Stand (mm): | 808 x 391.3 x 115 |
| GENERAL | |
| Regulations: | cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, TCO 9.0, EAC, UkrSEPRO |
| PACKAGE CONTENTS: | VG3457CV x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v2.0; Male-Male) x1, USB Type-C Cable (Male- Male; with Type-A adapter) x1, Quick Start Guide x1 |
| Recycle/Disposal: | Please dispose of in accordance with local, state or federal laws. |
| Warranty: | 5 Year Pick Up, Repair and Return |
| Power Management: | Energy Star standards, EPEAT |
| | |