

MPN: VLSP65AB

## Active Speaker Set, 2x30W, 5,25", Black

Professional stereo speakers in a rugged and durable design for meetingrooms, conferencerooms and classrooms.

Professional Speakers with Powersaving stand-by function.

The VLSP65AW is a step-up model with ballanced inputs and powerfull stereo speakersystem suitable for meeting- and conferencerooms, classrooms and more. Despite the compact design, the VLSP65AW deliver excellent sound through use of the integrated 2-way speaker units.

The VLSP65AW is equipped with a powerfull basswoofer and a combined midrange and tweeter unit which contributes to powerfull and great sound.



The speaker mounts are included and can be used in horizontal and vertical position. The system includes 10 meters speaker cable for use between the active and the passive unit.

- 2 x 30 Watt active speakers
- Automatic ECO mode after 90 seconds (0,5 Watt)
- Audio inputs: 2xRCA + Stereo 3,5 mm
- Switchable stereo / mono output
- One pair of speakers (one active + one passive)
- 140cm 230V Powercord

## Specifications

Audio	Frequency range	45 - 20000 Hz
	Impedance	4 Ω
	Peak Music Power Output (PMPO)	300 W
	RMS rated power	60 W
	Sensitivity	88 dB
	Speakers RMS power	30 W
Front speakers	Front speaker frequency range	45 - 20000 Hz
	Front speaker impedance	4 Ω
	Front speaker sensitivity	88 dB
	Front speaker tweeter diameter	1 "
	Front speaker type	2-way
	Front speaker woofer diameter (imperial)	5.25 "
	Front speakers RMS power	30 Watt
Loudspeakers	Audio output channels	2.0 channels
	Number of drivers	2
	Speaker type	2-way
	Tweeter	Yes
	Tweeter diameter (imperial)	1 "
	Woofer	Yes
	Woofer diameter (imperial)	5.25 "

Other features	Audio RCA inputs	1
	Front speaker frequency range	45 - 20000 Hz
	Front speaker impedance	4 Ω
	Front speaker sensitivity	88 dB
	Housing colour	White
	Magnetically shielded	Yes
	Speaker weight	6.36 g
Packaging content	Cables included	AC
	Mounting brackets included	Yes
	Mounting kit	Yes
Performance	Audio output channels	2.0 channels
	Certification	CE
	Housing material	Plastic
	Magnetically shielded	Yes
	On/off switch	Yes
	Product colour	Black
	Recommended usage	Universal
	RMS rated power	60 W
	Volume control	Rotary
Ports & interfaces	3.5 mm (1/8-inch) in	Yes
	6.35 mm (¼-inch) input	1
	Audio RCA inputs	1
	Connectivity technology	Wired
	Line-in connectivity	3.5 mm
Power	AC input voltage	230 - 240 V
	Current	1 A
	Power consumption (standby)	0.5 W
	Power consumption (typical)	75 W
	Power source	AC
	Power source type	AC
Technical details	Connector(s)	RCA, Minijack, Phoenix
	Frequency range	45 - 20000 Hz
	Impedance	4 Ω
	Number of speakers	2
	Peak Music Power Output (PMPO)	300 W
	Plug and Play	Yes
	Speaker placement	Wall-mountable
	Tweeter	Yes
Vendor information	Brand Name	Vivolink
	Warranty	3 Year(s)

Weight & dimensions	Cord length	10 m
---------------------	-------------	------

## Other images

