



VP2776T-4K - 27" COLORPRO™ 4K UHD IPS MONITOR WITH 100W THUNDERBOLT, RJ45, DCI-P3 AND HDR400

## **Key Features**

- Premium Thunderbolt 4 Connectivity
- Integrated Docking Station
- · High Resolution Dual Monitor Set-up
- Wide Color Gamut
- Pantone Validated Display
- Beautiful Ergonomic Design







27 DISPLAY

IPS PANEL 3840 x 2160 **RESOLUTION** 

## Product **Description**

The VP2776T-4K ColorPro™ Monitor is a professional-grade display engineered for creative excellence, offering stunning 4K resolution, precise DCI-P3 color accuracy, and HDR400 for an immersive visual experience. With integrated docking monitor features, including Thunderbolt 4 with 100W of power delivery, RJ45 Ethernet, and multiple connectivity options such as DisplayPort, HDMI, and a USB hub, it simplifies your workspace while ensuring stable performance. Thunderbolt technology allows this monitor to support dual 4K daisy chaining, allowing you to extend your display setup seamlessly for enhanced productivity.

## **Specifications**

More Information		
UPC	766907026061	
Screen Size	27	
Viewable Area (in.)	27	
Panel Type	IPS	
Display Resolution	3840 x 2160	
Display Resolution	4K (3840x2160)	
Static Contrast Ratio	2,000:1	
Dynamic Contrast Ratio	20,000,000:1	
Light Source	LED	

Brightness	400 cd/m2
Colors	1.07B
Color Space Support	10 bit (8 bit + FRC)
Aspect Ratio	16:9
Response Time (Typical GTG)	5ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
Refresh Rate	60Hz
PC Resolution (max)	3840 x 2160
Mac® Resolution (max)	3840 x 2160
USB Type A	3
USB Type C	15W x 1
3.5mm Audio Out	1
Ethernet LAN (RJ45)	1
HDMI 2.0 In	2
DisplayPort	1
Internal Speakers	3W (x2)
Eco Mode (Conserve)	221W
Eco Mode (optimized)	227W
Consumption (typical)	235W
Consumption (max)	250W
Voltage	DC 24V
Stand-by	0.5W
Power Supply	External
Cable Organization	No
Physical Controls	Joystick key: Up, Right, Down, Left, Center; Power
On Screen Display	Input Select, Color Mode, ViewMode, Audio Adjust, Setup Menu
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	HDMI 2.1, DisplayPort, Thunderbolt: 30 ~ 150 KHz
Frequency Vertical	HDMI 2.1, DisplayPort, Thunderbolt: 24 ~ 75 Hz
Height Adjust	120 mm / 4.7 in
Swivel	120º
Pivot (Right/Left)	90º / 90º

Tilt (Forward/Back)	3º / 22º
Net (lbs)	16.8
Net Without Stand (lbs)	9.3
Gross (lbs)	28.9
Net (kg)	7.6
Net Without Stand (kg)	4.2
Gross (kg)	13.1
Packaging (in.)	28.3 x 20.3 x 9.0
Physical (in.)	24.16 x 17.73 ~ 22.46 x 9.21
Physical Without Stand (in.)	24.16 x 14.32 x 2.20
Packaging (mm)	720.0 x 515.0 x 228.0
Physical (mm)	613.7 x 450.36 ~ 570.36 x 234
Physical Without Stand (mm)	613.7 x 363.85 x 55.8
Regulations	613.7 x 363.85 x 55.8
Package Contents	VP2776T-4K Display, DisplayPort Cable, HDMI Cable, Thunderbolt4 Cable, USB-C to USB-A Cable, Power Adaptor, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	Three-year limited warranty on parts, labor and backlight
UPC: 766907026061	

**Contact Sales** 

ViewSonic.com

888.881.8781 email: salesinfo@viewsonic.com