

## Key Features

- SuperClear® IPS panel ensures wide viewing angles and vibrant colours for immersive gaming
- Experience fluid gameplay with the blazing-fast 180hz refresh rate
- Swift 1ms MPRT ensures razor-sharp visuals in fast-paced gaming
- AMD FreeSync™ technology eliminates screen tearing and reduces stuttering
- HDR10 delivers stellar contrast and colour accuracy



## Product **Description**

The ViewSonic VX2779J-HD-PRO is a versatile 27-inch Full HD monitor designed to elevate your visual experience, whether you're working or gaming. With a high 180Hz refresh rate and lightning-fast 1ms MPRT response time, this monitor ensures smooth visuals and minimal input lag – ideal for gamers seeking a competitive advantage. Equipped with SuperClear® IPS technology, it boasts wide viewing angles and breathtaking visuals, perfect for immersive gaming sessions, creative endeavors, and efficient office work. Beyond performance, the monitor's sleek design elevates your workspace aesthetics, combining form and function for a complete package.

Visit Us www.viewsonic.com

DICDLAY	VX27733 FIB F RO 27 TOOFIZ	CONTROLS	ou ranguom
Display Size (in ):	27	CONTROLS	Key 1 (favorite), Key 2, Key 3,
Display Size (in.):  Viewable Area (in.):	27	Physical Controls:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)
Panel Type:	IPS Technology	On Conson Bianton	Input Select, Audio Adjust,
Resolution:	1920 x 1080	On Screen Display:	ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
		OPERATING CONDITIONS	
Resolution Type:	FHD (Full HD)	Temperature:	32°F to 104°F (0°C to 40°C)
Static Contrast Ratio:	1,000:1 (typ)	Humidity (non-condensing):	20% to 90%
Dynamic Contrast Ratio:	50M:1	WALL MOUNT	
High Dynamic Range:	HDR10	VESA Compatible:	100 x 100 mm
Light Source:	LED	INPUT SIGNAL	
Brightness:	250 cd/m² (typ)	Frequency Horizontal:	30 ~ 202KHz
Colors:	16.7M	Frequency Vertical:	48 ~ 180Hz
Color Space Support:	8 bit (6 bit + FRC)	VIDEO INPUT	
Aspect Ratio:	16:9	Digital Sync:	TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.4)
Response Time (MPRT):	1ms	ERGONOMICS	Displays of (V1.4)
Viewing Angles:	178º horizontal, 178º vertical	Height Adjust (mm):	130
Backlight Life (Hours):	30000 Hrs (Min)	Swivel:	90°
Curvature:	Flat	Tilt (Forward/Back):	-5° / 22°
Refresh Rate (Hz):	180	Pivot (Right/Left):	90° / 90°
Variable Refresh Rate Technology:	FreeSync	WEIGHT (IMPERIAL)	30 7 30
Low Blue Light:	Software solution	Net (lbs):	12.3
Flicker-Free:	Yes	Net Without Stand (lbs):	8
Color Gamut:	NTSC: 72% size (Typ) sRGB: 104% size (Typ)	Gross (lbs):	16.3
Pixel Size:		WEIGHT (METRIC)	
	0.311 mm (H) x 0.311 mm (V)	Net (kg):	5.6
Surface Treatment:  COMPATIBILITY	Anti-Glare, Hard Coating (3H)	Net Without Stand (kg):	3.7
PC Resolution (max):	1920×1080	Gross (kg):	7.4
Mac® Resolution (max):	1920×1080	DIMENSIONS (IMPERIAL) (W	/XHXD)
mace Resolution (max).	Windows 10/11 certified; macOS	Packaging (in.):	26.7 x 19.4 x 6.6
PC Operating System:	tested	Physical (in.):	24.21 x 15.68~20.80 x 8.99
Mac® Resolution (min):	1920×1080	Physical Without Stand (in.):	24.21 x 14.32 x 1.81
CONNECTOR		DIMENSIONS (METRIC) (WX	HXD)
3.5mm Audio Out:	1	Packaging (mm):	677 x 494 x 168
HDMI 1.4:	2	Physical (mm):	615 x 398.3~528.3 x 228.3
DisplayPort:	1	Physical Without Stand (mm):	615 x 363.8 x 46
Power in:	DC Socket (Center Positive)	GENERAL	
POWER		Regulations:	CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC,
Eco Mode (Conserve):	24W	Negulations.	UkrSEPRO
Eco Mode (optimized):	28W	PACKAGE CONTENTS:	VX2779J-HD-PRO x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1
Consumption (typical):	30W		
Consumption (max):	34W		
Voltage:	AC 100-240V	Recycle/Disposal:	Please dispose of in accordance
Stand-by:	0.5W	rtobyolo/Dioposal.	with local, state or federal laws.
Power Supply:	External Power Adaptor	Warranty:	*Warranty offered may differ from market to market
ADDITIONAL HARDWARE			
Kensington Lock Slot:	1		
Oakla Oanania "	V		

Yes

Cable Organization: