

## **Key Features**

- Instant, secure access to your digital workspace using Windows Hello
- Crystal-clear video with a built-in Zoom® Certified 5MP pop-up camera with LED fill lights, microphone, and 5W speakers
- Integrated docking station with Ethernet, Daisy Chain capability, and dual USB-C ports for seamless connectivity
- 15W quick charging for mobile devices via USB-C connection
- Flicker-free, low blue light screen with Eye ProTech+ for always-on eye protection



# Product **Description**

The VG2757V-2K is a 27" QHD videoconferencing monitor featuring Windows Hello compatibility. It boasts a Zoom® Certified QHD pop-up webcam that delivers exceptional audiovisuals and discreetly hides away for privacy when not in use. With Windows Hello, it ensures secure facial recognition for swift and convenient logins, eliminating the dependency on passwords. Equipped with 90W and 15W USB-C ports, ethernet, and daisy-chain support, the VG2757V-2K serves as a complete integrated docking station for charging, data transfer, and network connectivity, effectively reducing cable clutter. Its extensive ergonomic flexibility allows tilt, swivel, pivot, and height adjustments for various workflows. Enhanced by vDisplay Manager software for efficient multitasking and on-screen display controls, it offers a comprehensive videoconferencing solution.

- 1. 5W Speakers 2. Menu Control Panel 3. LED Fill Light 4. IR Sensor

- 5. Microphone
- 6. USB Type C (Quick Charging) 7. Audio Out
- 8. Power In 9. USB Type A 3.2 DownStream\*3 10. Ethernet (RJ45) 11. DisplayPort Out 12. USB Type C 13. DisplayPort

- 13. DisplayPort
- 14, HDMI

15. VESA Compatible (Wall Mount 100x100mm)

**Visit Us** 

www.viewsonic.com



17:07	viewSonic	VG2757V-2K 27" QHD 100Hz Video Conf
DISPLAY		07
Display Size (in.):		27
Viewable Area (in.)	:	27
Panel Type:		IPS Technology
Resolution:		2560 x 1440
Resolution Type:		QHD (Quad HD)
Static Contrast Rat		1,300:1 (typ)
Dynamic Contrast I	Ratio:	80M:1
Light Source:		LED
Brightness:		350 cd/m² (typ)
Colors:		16.7M
Color Space Suppo	ort:	8 bit true
Aspect Ratio:		16:9
Response Time (Ty	pical GTG):	5ms
Response Time (G	TG w/OD):	5ms
Viewing Angles:		178° horizontal, 178° vertical
Backlight Life (Hou	rs):	30000 Hrs (Min)
Curvature:		Flat
Refresh Rate (Hz):		100
Low Blue Light:		Hardware solution
Flicker-Free:		Yes
Color Gamut:		NTSC: 76% size (Typ) sRGB: 108% size / 100% coverage (Typ)
Pixel Size:		0.233 mm (H) x 0.233 mm (V)
Surface Treatment:		Anti-Glare, Hard Coating (3H)
COMPATIBILITY		
PC Resolution (ma	x):	2560×1440
Mac® Resolution (r	max):	2560x1440
PC Operating Syste	em:	Windows 10/11 certified; macOS tested
Mac® Resolution (r	min):	2560x1440
USB 3.1 Type C - E	Downstream:	1 (15W power charger)
USB 3.2 Type A Do		3
USB 3.2 Type C Up DisplayPort Alt mod	Stream;	1 (90W power charger)
3.5mm Audio Out:		1
HDMI 2.0:		1.
DisplayPort:		1
DisplayPort Out:		1
Power in:		3-pin Socket (IEC C14 / CEE22)
Ethernet LAN (RJ4	5):	1
AUDIO		
Internal Speakers:		5Watts x2
POWER		
Eco Mode (Conserv	ve):	24.36W
Eco Mode (optimize	ed):	26.75W
Consumption (typic	al):	29.77W
Consumption (max		34.29W
Voltage:		AC 100-240V
Stand-by:		0.5W
Power Supply:		Internal Power Supply
ADDITIONAL HA	RDWARF	
Kensington Lock Si		1
Webcam:		5.0M pixel
Cable Organization	,	Yes
		Yes
Microphone: CONTROLS		100
Physical Controls:		Key 1 (eye), Key 2, Key 3, Key 4, Key 5, Key 6 (power)
On Screen Display:		Input Select, Conference Mode, ViewMode, Color Adjust,
		Manual Image Adjust, Setup Menu
DEDATING CON	במטוווחי	
OPERATING CON		32°E to 104°E (0°C to 40°C)
Temperature:	loneina):	32°F to 104°F (0°C to 40°C)
Temperature: Humidity (non-cond	lensing):	32°F to 104°F (0°C to 40°C) 20% to 90%
Temperature: Humidity (non-cond	densing):	20% to 90%
Temperature: Humidity (non-cond WALL MOUNT VESA Compatible:	lensing):	
Temperature: Humidity (non-cond WALL MOUNT VESA Compatible: INPUT SIGNAL		20% to 90% 100 x 100 mm
Temperature: Humidity (non-cond WALL MOUNT VESA Compatible: INPUT SIGNAL Frequency Horizon	tal:	20% to 90% 100 x 100 mm 15 ~ 150KHz
Temperature: Humidity (non-cond WALL MOUNT VESA Compatible: INPUT SIGNAL Frequency Horizon Frequency Vertical	tal:	20% to 90% 100 x 100 mm
Temperature: Humidity (non-cond WALL MOUNT VESA Compatible: INPUT SIGNAL Frequency Horizon	tal:	20% to 90% 100 x 100 mm 15 ~ 150KHz

RO	• ^	 $\overline{}$	 ١.

Height Adjust (mm):	110
Swivel:	120°
Tilt (Forward/Back):	-5° / 40°
Pivot (Right/Left):	90° / 90°

### WEIGHT (IMPERIAL)

 Net (lbs):
 17.7

 Net Without Stand (lbs):
 12

 Gross (lbs):
 25.3

#### WEIGHT (METRIC)

 Net (kg):
 8

 Net Without Stand (kg):
 5.5

 Gross (kg):
 11.5

#### DIMENSIONS (IMPERIAL) (WXHXD)

Packaging (in.): 27.1 x 17.8 x 8.9

Physical (in.): 24.12 x 16.67~21 x 8.55

Physical Without Stand (in.): 24.12 x 15.36 x 2.24

#### DIMENSIONS (METRIC) (WXHXD)

 Packaging (mm):
 689 x 452 x 225

 Physical (mm):
 612.7 x 423.38-533.38 x 217.24

 Physical Without Stand (mm):
 612.7 x 390.15 x 56.9

#### GENERAL

cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC,
NOM, Mexico Energy, CE, CE EMC, CB, RoHS, ErP,
REACH, WEEE, TCO 9.0, EAC, UkrSEPRO, BSMI, RCM,
BIS

VG2757V-2K x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI
Cable (v2.0; Male-Male) x1, USB Type-C Gen2 Cable
(Male-Male) x1, USB Type-C to Type-A 3.2 Gen1 Cable
(Male-Male) x1, Quick Start Guide x1

Recycle/Disposal:

Please dispose of in accordance with local, state or federal laws.

Warranty:

\*Warranty offered may differ from market to market

Power Management:

Energy Star standards, EPEAT

