

Key **Features**

- 3rd generation laser phosphor technology with up to a 30,000-hour lifespan
- 5,000 ANSI Lumens
 offering bright images in
 any environment
- Up to 300" ultra large screen with lower costper-inch
- Compact size and light weight reducing cost of transportation and installation
- Installation flexibility: 1.3x optical zoom, H/V keystone, 360° projection, and portrait mode



Product **Description**

The V52HD belongs to ViewSonic's Luminous Superior series, a lamp-free high-brightness projector lineup designed for commercial and educational spaces. With its adoption of the 3rd generation laser phosphor technology, it delivers 5,000 ANSI Lumens for up to 30,000 hours, ensuring bright and vivid images without lamp replacement. The lamp-free design offers an eco-friendly and cost-effective solution, while the projector's lightweight and compact design reduces transportation costs. With up to 300" projection in 1080p Full HD with high native contrast, it is well-suited for boardrooms, lecture halls, and public spaces. This projector features a 1.3x optical zoom, H/V keystone, 4 corner adjustment, 360° projection, and a portrait mode for easy setup and versatile applications.



- 1. Front IR

- 1. Front IR 2. Lens 3. Focus Ring 4. HDMI x2 5. RS232 6. USB-A (5V/1.5A, Service) 7. Audio Out

- 8. DC In 9. Zoom Ring 10. Top IR 11. Keypad 12. Power Button

Visit Us

www.viewsonic.com

SPECIFICATION

SPECIFICATION		(
Native Resolution:	1920×1080	
Brightness:	5000 (ANSI Lumens)	
Contrast Ratio:	2,000,000:1	
Display Color:	1.07 Billion Colors	
Light Source Type:	Laser Phosphor	
Light Source Life (hours) with Normal Mode:	20000	
Light Source Life (hours) with SuperEco Mode:	30000 (Eco)	
Lens:	F=2.43-2.78, f=16.90- 21.61mm	
Projection Offset:	132%+/-5%	
Throw Ratio:	1.13-1.47	
Optical Zoom:	1.3X	
Digital Zoom:	0.8x-2.0x	
Image Size:	30"-300"	
Throw Distance:	0.75-9.76m (100"@2.50m)	
Keystone:	H:+/-30° , V:+/-30°	
Audible Noise (Normal):	32dB	
Audible Noise (Eco):	26dB	
Input Lag:	33.3ms	
Resolution Support:	VGA(640 x 480) to WUXGA RB(1920 x 1200) *RB-Reduced Blanking	
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p	9
Horizontal Frequency:	15K-102KHz	
Vertical Scan Rate:	24-120Hz	
INPUT		
HDMI:	2 (HDMI 1.4/ HDCP 1.4)	
OUTPUT		(
Audio-out (3.5mm):	1	
Speaker:	15W	
USB Type A (Power):	1 (5V/1.5A)	
CONTROL		
RS232 (DB 9-pin male):	1	
USB Type A (Services):	1 (share with USB A Output)	

OTHERS		
Power Supply Voltage:	Input: 100~240V Output: 19.5VDC / 11.79A	
Power Consumption:	Normal: 210W Standby: <0.5W	
Operating Temperature:	0~40°C	
Carton:	Brown	
Net Weight:	3.00kg	
Gross Weight:	4.70kg	
Dimensions (WxDxH) with Adjustment Foot:	286x216x129mm	
Packing Dimensions:	400x280x155mm	
OSD Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S- Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, Arabic, Vietnamese, Hungarian, Norsk, total 23 languages	
User Guide Language:	English, S-Chinese, T-Chinese, Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, total 20 languages	
STANDARD ACCESSORY		
Power Cord:	1	
Remote Control:	1	
QSG:	Yes	
Warranty:	*Warranty offered may differ from market to market	
OPTIONAL ACCESSORY		
Wall/Ceiling Mount:	PJ-WMK-007	
Carry Bag:	PJ-CASE-008	

Copyright © ViewSonic Corporation 2000-2024. All rights reserved.