

Photon Life PK32

Photon Life PK32 Home Projector

PHOTON[®]
LIFE



- **4K UHD 4LED Technology** - Enjoy bright, immersive entertainment with 1100 lumens of vivid clarity. Whether it's movie night or gaming with friends, the Photon Life PK32 delivers crisp and vibrant visuals.
- **Super-fast Gaming** - Ultra-low input lag of 4.6ms gives gamers real-time responsiveness, leaving your competition in the dust.
- **Place and Play** - ToF Auto vertical keystone and focus automatically adjusts for a clear, sharp and perfectly straight image.
- **Built in speakers** - No need for extra sound equipment thanks to the two built-in 5W speakers.



Level up the way you enjoy your entertainment with the Photon Life PK32.

Photon Life PK32 – cinematic 4K anywhere. Powered by 4LED tech with 1100 ISO lumens, 95% DCI-P3 colour and ultra-low 4.6ms input lag for smooth gaming. Enjoy 150" big-screen magic, USB-C connectivity and smart auto focus with ToF tech. Just plug in and play.

Specifications

UPC: 796435 44 807 3, EAN: 5055387668973, Colour: Black



Display/image	
Display technology	DLP®
Resolution	UHD (3840x2160)
Brightness	1,100 lumens
Brightness (HK)	2,000
Contrast ratio	250,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3, 16:9
Keystone correction - horizontal	40°
Keystone correction - vertical	40°
Has vertical auto keystone correction	Yes
Horizontal scan rate	23-240Khz
Vertical scan rate	15-255Hz
Uniformity	90%
Screen size	1.52m ~ 3.81m (60" ~ 150") diagonal
Lamp info	
Light source type	4 LED
LED life	30,000 hours
Optical	
Throw ratio	1.12:1 ~ 1.46:1
Projection distance (m)	1.497m - 4.848m
Zoom	1.3
Zoom type	Manual
Focal length (mm)	11.9 ~ 15.5
Native offset	105%
Connectivity	
Connections	Inputs 2 x HDMI 2.0 (eARC), 1 x USB-C Outputs 1 x USB-A power 2A, 1 x Audio 3.5mm
General	
Noise level (min)	30dB
Noise level (max)	32dB
PC compatibility	VGA, SVGA, XGA, SXGA, QuadVGA, SXGA+_60, UHGA_60, WXGA, 1680x1050_60, 1366x768_60, 1920x1080_RB, 1920x1200_RB
2D compatibility	480i, 480p, 576i, 576p, 720p_60, 720p_50, 1080i_60, 1080i_50, 1080p_60, 1080p_50, 1080p_24, 1080p_23.98, 1080p_30, 2160/24P, 2160/25P, 2160/30P, 2160/50P, 2160/60P
3D compatibility	Yes (Support DLP 3D PC source 50/60/100/120Hz and Video source 50/60Hz)
Security	Kensington Lock
IP rating	IP5X (Optical Engine only)
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
24/7 operation	Yes
360° operation	Yes
Operating conditions	Operating Altitude: Without high altitude mode, 0°C~35°C@1499m above sea level. With high altitude mode, 0°C~30°C@1500m~3000m above sea level. Non-Operating Altitude: 30°C@0~12,200m above sea level.
Remote control	Yes
Speaker count	2
Watts per speaker	5W
In the box	Adaptor (150W) Remote control Basic user manual 2x AAA Battery HDMI Cable
Input lag	4.60ms
Power	
Power supply	VAC 100-240V (50/60Hz)
Power consumption (standby)	0.5W
Power consumption (min)	69W
Power consumption (max)	162W
Weight and dimensions	
Dimensions (W x D x H) mm	238 x 215 x 130
Gross weight	4 kg
Net weight	2.2 kg