

## NEC PA1004UL

Professional Advanced LCD Laser Installation Projector

# Datasheet



### A new class of silent projection

Now even larger spaces can benefit from NEC's innovation in super-silent technology with the 10,000 lumens PA1004UL laser projector, ensuring all attention is focused on the stunning image delivery.

Featuring unprecedented White Point performance, factory pre-calibrated for the perfect white, 12-bit colour signal processing and wide colour space, the audience will experience extraordinarily vivid colour saturation and contrast levels.

The enhanced sealed optical engine allows a filter-free design, IP5X rated against dust ingress - no possibility of dust contaminating the LCD panels for long-term picture stability and brilliant colour brightness. What's more, with our filterless LCD projector design and no lamp replacement, service costs are dramatically reduced for a low cost of ownership and up to 20,000 hours life-time.

Fully compatible with previous generation lamp-based PA Series mechanical lenses, NEC customers can easily make the transition to benefit from the latest laser technology. The PA1004UL is a professional installation projector featuring advanced installation capabilities as demanded by higher education, leisure and museum applications.

### Benefits

**No lamp replacement** - up to 20,000 h maintenance free operation possible due to Laser Light

Source.

**No filter service required** – a completely sealed optical laser LCD engine allows a filter-free design. Brilliant colour brightness is maintained and servicing costs need no longer feature in your budget.

**Super Silent operation** – patented sealed light engine incorporating innovative fan design not only protects against dust ingress but dramatically reduces noise.

**Impress with vivid colour & contrast** – brilliant white and wide colour space with high dynamic contrast supporting HDR10 standard via HDMI interface.

**Incredible visualisation capabilities** – impressive free tilt and portrait installation capability, unique geometric adjustment, picture in picture, tiling, 3D support and camera based blending/stacking up to 4K.

## Product Information

Product Name	NEC PA1004UL
Product Group	Professional Advanced LCD Laser Installation Projector
Order Code	60004512 (WH), 60005160 (BK)

## Image

Projection Technology	3LCD Technology			
Native Resolution	1920 x 1200 (WUXGA)			
Aspect Ratio	16:10			
Contrast Ratio	3000000:1			
Brightness	9000 Lumen (approx. 80% in Eco Mode), with std. optional lense; compliant with ISO21118-2012			
Brightness (Boost Mode)	10000 Lumen			
Lamp	Laser Light Source			
Light Source Life [hrs]	20000 <sup>1</sup>			
Lens	4 motorized lens options; 5 manual lens options			
Lense Adjustment	Motorized and manual (depending on lens)			
Lens shift	H:±20, V:+10,-50			
Keystone correction	+/- 40° manual horizontal / +/- 40° manual vertical			
Projection Factor	depending on lens selection (std. option NP41ZL at 1.3-3.02:1)			
Projection Distance [m]	0.7 – 50.9			
Screen Size (diagonal) [cm] / [inch]	Maximum: 1,270 / 500"; Minimum: 101.6 / 40"			
Zoom	Motorized and manual (depending on lens)			
Focus Adjustment	Motorized and manual (depending on lens)			
Supported Resolutions	1080i/50/60; 1080p/24/25/30/ 50/60; 1920x1200 (WUXGA) - 640x480 (VGA);	2048 x 1080 (2k); 2560 x 1600 (WQXGA); 4096 x 2160 (4k);	480i/50; 480p/60; 576i/50; 576p/50; 720p/50;	720p/60
Frequency	Horizontal: analog: 15/24-100 kHz, digital: 15/24-153 kHz; Vertical: analog: 48-120 Hz, digital: 48-120 Hz			

## Connectivity

RGB (analog)	Input: 1 x Mini D-sub 15-pin, compatible to component (YPbPr)
Digital	Input: 1 x DisplayPort; 1 x HDBaseT; 2 x HDMI™ supporting HDCP 2.2 Output: 1 x HDBaseT supporting HDCP 2.2

Audio	Input: 1 x DisplayPort Audio support; 1 x HDBaseT audio support; 2 x 3.5 mm Stereo Mini Jack for Computer analog; 2 x HDMI audio support Output: 1 x 3.5 mm Stereo Mini Jack (variable)
Control	Input: 1 x 3.5 mm Stereo Mini Jack (Wired Remote); 1 x D-Sub 9 pin (RS-232), Ethernet
LAN	1 x RJ45
USB	1 x Type A (USB 2.0 high speed)
3D Sync	Output: 1 x Mini DIN 3pin

## Remote Control

Remote Control	Audio Control; Digital Zoom; Geometric Correction; ID Select; ID set; Power (On-OFF); Select (up, down, left, right); Shutter function; Source Select; Test Picture; Zoom/Focus and Lens Shift Control
----------------	--

## Electrical

Power Supply	100-240 V AC; 50 - 60 Hz
Power Consumption [W]	725 (Normal) / 395 (Eco) / 0.8 (Network Stand-by) / 0.28 (Stand-by)

## Mechanical

Dimensions (W x H x D) [mm]	599 x 208 x 490 (without lens and feet)
Weight [kg]	24.4
Fan Noise [dB (A)]	32 / 35 (Eco / Normal)
Colour Versions	Black; White

## Environmental Conditions

Operating Temperature [°C]	0 to 40
Operating Humidity [%]	20 to 80 non-condensing
Storage Temperature [°C]	-10 to 50
Storage Humidity [%]	20 to 80 non-condensing

## Ergonomics

Safety and Ergonomics	CE; EAC; ErP; RoHS; TUEV Type Approved
-----------------------	--

## Additional Features

Special Characteristics	3D ready; 4K/60Hz interfaces; Active 3D; AMX Beacon; Built-in Display/Multiscreen Splitter; Cinema Quality Picture (CQP) Processing for best image quality; Crestron RoomView; DICOM simulation; Digital 3D Reform™; Direct Power-Off Function; Edge Blending Function; Free Tilt; Geometric Correction; HDBaseT; HDBaseT-out signal connection; HDR10 Support; High Altitude Mode; Hollywood Quality Video Processing for best image quality; HTTP Browser Control; IP5X/IP6X rated; Keystone Correction (H=±40°, V=±40°); LAN control; Lens Memory; Lens Shift (vertical +0.5 max/-0.1 max, horizontal ± 0.3 max.); Light Source Adjustment; Manual Wall Color Correction; Multi-Screen compensation mode; NaViSet Administrator 2; Optional User Logo; OSD with 27 languages; Password Security System; PIP/Side by Side, HDMI - Input; PJ LINK; Portrait Setting; Rec2020 to Rec709 colour conversion; RS-232 Control; Seamless Switching; Stacking Function; Test Pattern; Timer-Function; UHD player support; Up to 20,000 hrs Light Source Life; Virtual Remote for direct PC control
-------------------------	--

## Green Features

Energy Efficiency	ECO scheduler; Intelligent power management; Less than 0.3W stand-by power; Longer light source life; Software scheduling; Timer function
Ecological Materials	100% recyclable packaging; Downloadable manuals
Ecological Standards	ErP compliant

## Warranty

Projectors	3 years pan-European service
Light Source	3 years or 10000h (whatever comes first)

## Shipping Content

Shipping Contents	IR Remote Control (RD-480E); Power Cord; Projector; Quick Setup Guide; Users Manual on CD-ROM
-------------------	---

## Optional Accessories

Optional Accessories	10 optional bayonet lenses; Cable Cover (NP13CV-W, NP13CV-B); Universal Ceiling Mounts (PJ02UCMPF)
Lenses - motorized	NP40ZL (0.79-1.11:1); NP41ZL (1.3-3.02:1); NP43ZL (2.99-5.93:1); NP44ML-PA4 (0.32:1); NP50ZL (0.6-0.75:1)
Lenses - manual	NP11FL (0.79:1); NP12ZL (1.16-1.52:1); NP13ZL (1.46-2.95:1); NP14ZL (2.9-4.68:1); NP15ZL (4.59-7.02:1)

<sup>1</sup> 50% of initial brightness at the end of specified laser life time at 25 degree ambient temperature.

\* This product has been equipped with a laser module and is classified as Class1 of IEC60825-1 Ed3 2014 and is classified as RG3 of IEC62471-5 Ed1 2015.

DO NOT LOOK DIRECTLY INTO THE BEAM.



CE



TUEV Type Approved



ErP



RoHS

This document is © 2025 Sharp NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 22.02.2025