

MPN: AUDIOPACK4

Audiopack Subwoofer 8" 50W + 4 x ceiling speakers

Vivolink Audio pack is the perfect speaker bundle for office or meeting rooms.

The four ceiling speakers (VLSPMTC60WT 2-way 70w) are discrete white and can easily be mounted in the ceiling. It will give a clean and almost invisible installation.


The active Sub-woofer is fully automated and will add bass to the sound and will deliver speaker power to the ceiling speakers.

Sub-woofer is designed to be mounted over ceiling or under furniture

Ideal for meeting rooms, hotels and auditoriums.

It have line input and loop out for active sattelite speakers.

Sub-woofer can also be used together with passive sattelite speakers using the internal power amplifier for satellite speakers on 2 x 25W



- For rooms up to 200m2

- Power effect for sub-woofer: 50 Watts

- Power effect for passive ceiling speakers:

(VLSPMTC60WT) 2x25Watts

- Inputs: 100V, Balanced in and RCA line in

- Bluetooth input for speaker out only (not supported for line-out)

- Outputs: RCA line out and Speaker out 2x 25W

- Line out for active speakers (VLSP60/65/61/70)

- Frequency range: 80Hz-20kHz

- Impedance: 8 Ohm

- Active powered Subwoofer 8" 50W
- 2x25W speaker output + line- out
- 4 x VLSPMTC60WT 2-way 70w frameless ceiling speakers
- Silent on/off via automatic ECO mode after 90 seconds (less than 0,5 Watt)
- Audio inputs: 2xRCA + 100V + Balanced input + Bluetooth for (speaker out only)

Specifications

Amplifier	Amplifier	Built-in
	Amplifier class	D
	Amplifier output power	110 W
	Amplifier output power (tweeter)	30 Watt
	Amplifier output power (woofer)	50 Watt

Amplifier	Number of amplifier channels	3 channels
Audio	Crossover frequency	200 Hz
	Frequency range	40 - 20000 Hz
	Impedance	4 Ω
	RMS rated power	110 W
	Speakers RMS power	60 W
	Subwoofer RMS power	50 W
Loudspeakers	Audio output channels	2.1 channels
	Number of drivers	3
	Speaker placement	Ceiling-mountable, Wall-mountable
	Subwoofer RMS power	50 W
	Woofer	Yes
	Woofer diameter (imperial)	8 "
Other features	Accessories included	AC Power Cord
	Adaptor plug	EU
	Audio (L/R) in	1
	Case colour	Black
	Front speaker frequency range	80 - 20000 Hz
	Front speaker impedance	4 Ω
	Housing colour	Black
	Manual	Yes
	Speaker weight	6.36 g
Packaging content	Cables included	AC
	Mounting brackets included	Yes
Performance	Certification	CE
	Housing material	Plastic
	Magnetically shielded	Yes
	On/off switch	Yes
	Product colour	Black
	Volume control	Rotary
Ports & interfaces	3.5 mm (1/8-inch) in	Yes
	6.35 mm (¼-inch) input	1
	Audio RCA inputs	1
	Connectivity technology	Wired
Power	AC input voltage	230 - 240 V
	Current	1 A
	Power consumption (standby)	0.5 W
	Power consumption (typical)	75 W
	Power source type	AC
Technical details	Warranty period	3 year(s)

Vendor information

Brand Name	Vivolink
Warranty	3 Year(s)

Other images

