

MPN: VLSP60AW

## Active Speaker Set, 2x30W, 5,25", White

Professional stereo speakers in a rugged and durable design for meetingrooms, conferencerooms and classrooms.

### Professional Speakers with Powersaving stand-by function.

The PROSPEAKERS is a powerfull stereo speakersystem suitable for meeting- and conferencerooms, classrooms and more. Despite the compact design, the PROSPEAKERS deliver excellent sound through use of the integrated 2-way speaker units.

The PROSPEAKERS is equipped with a powerfull basswoofer and a combined midrange and tweeter unit which contributes to powerfull and great sound.

The PROSPEAKERS mounts both standing and via wallmount and can even be used in horizontal position. The system includes 10 meters speaker cable for use between the active and the passive unit.

Note: Passive speaker weight: 1950g, Active speaker weight: 3010g, Mounts weight: 392g each.

Only connect to one if the inputs. Either RCA or Minijack Connector.

There is RCA and Minijack 3,5mm input on the speaker, the two terminal types are connected together inside the speaker so both input terminals are open for sound inputs.

- 2 x 30 Watt active speakers
- Automatic ECO mode after 90 seconds (0,5 Watt)
- Audio inputs: 2xRCA + Stereo 3,5 mm
- Switchable stereo / mono output
- One pair of speakers (one active + one passive)
- 140cm 230V Powercord



## Specifications

Audio	Frequency range	45 - 20000 Hz
	Impedance	4 Ω
	Peak Music Power Output (PMPO)	300 W
	RMS rated power	60 W
	Sensitivity	88 dB
	Speakers RMS power	30 W
Loudspeakers	Audio output channels	2.0 channels
	Number of drivers	2
	Speaker type	2-way
	Tweeter	Yes
	Tweeter diameter (imperial)	1 "
	Woofer	Yes
	Woofer diameter (imperial)	5.25 "

Other features	Front speaker frequency range	45 - 20000 Hz
	Front speaker impedance	4 Ω
	Front speaker sensitivity	88 dB
	Housing colour	White
	Magnetically shielded	Yes
	Speaker weight	6.36 g
Packaging content	Cables included	AC
	Mounting brackets included	Yes
Performance	Certification	CE
	Housing material	Acrylonitrile butadiene styrene (ABS), Polyvinyl chloride (PVC)
	Magnetically shielded	Yes
	On/off switch	Yes
	Product colour	White
	Recommended usage	Universal
	Volume control	Rotary
Ports & interfaces	3.5 mm (1/8-inch) in	Yes
	3.5 mm connector	Yes
	Audio RCA inputs	1
	Connectivity technology	Wired
Power	AC input voltage	230 - 240 V
	Current	1 A
	Power consumption (standby)	0.5 W
	Power consumption (typical)	75 W
	Power source type	AC
Vendor information	Brand Name	Vivolink
	Warranty	3 Year(s)
Weight & dimensions	Cord length	10 m

## Other images

