

MPN: VLUSBCHUB2V2

USB-C HUB for conference rooms

Vivolink 4K USB-C HUB – Your all-in-one solution for video conferencing systems. Connect all your equipment, just like you would with a docking station for your computer.

The VLUSBCHUB2V2 is your key to effortless conferencing. Designed as a 4K USB-C Hub, it allows you to connect multiple devices via USB and share content seamlessly on a single screen.

This Hub is designed to be fixed either under, or on top of, the desk to support all connections within a conference setting.

The Hub provides power for the connected device, thus reducing the need for extra unnecessary power cables. DIP switch on product can control powering of USB devices, constant power or auto power that follows HOST connection. The HDMI output delivers both 4K video and sound from the device, while the LAN port provides cabled network connection to the laptop.

Supports:

- HDMI 1.4, 4K@30Hz 4:4:4
- USB-C input supports 100W power delivery
- Supports USB3.2 Gen2 data transfer via USB-C
- 2 USB3.2 Gen 1 and 1 USB2.0 KVM for camera, keyboard and mouse
- Supports USB power management, maximum power delivery shared for all four ports is 2Amp
- Ethernet Gigabit LAN
- Plug and Play

Ensure to use cable PROUSBCMM* for the connection from PC to HUB.

The maximum recommend length of cable is 5m (PROUSBCMMS5)

The following formats are supported:

DP Alt Mode, DisplayPort Supported products: Windows PC, Apple MacBook including iPad Pro M2

Recommended HDMI cables for long distance is: PROHDMIOP20

Package Content:

- 1 x HUB
- 1 x 100W USB-C PSU incl. mount for PSU
- 1 x UK Power Plug (Type G)
- 1 x EU Power Plug (Type C)

- 1x Host USB3.2 Gen2 10 Gbit connector for PC connection
- 1x HDMI output 4K@30Hz 4:4:4 resolution
- 2x USB3.0 input 5 Gbit (USB3.2 Gen1)
- 1x USB-C input 5 Gbit (USB3.2 Gen1)
- 1x USB2.0 input 480 Mbps
- USB power ON or Auto controlled via DIP switch
- 1x Ethernet RJ45 Gigabit input
- 1x USB-C power input 100W
- Including a 100W charger that will fast charge the laptop

Specifications



Design	Housing material	Metal
Logistics data	Master (outer) case height	5 cm
	Master (outer) case length	33 cm
	Master (outer) case width	16.5 cm
Performance	HDMI output	Yes
	HDMI ports quantity	1
	HDMI version	1.4
	Maximum resolution	3840 x 2160 pixels
	Number of displays supported	1
	Refresh rate at maximum resolution	30 Hz
	RoHS compliance	Yes
	USB connector form factor	Straight
	USB connector gender	Male
	USB connector type	USB Type-C
	USB version	3.2 Gen 1 (3.1 Gen 1)
Vendor information	Brand Name	Vivolink
	Warranty	5 Year(s)

Other images

