

MPN: VLHDBSP1X4V2

## HDBT 2.0 splitter 1x4 with loop

VLHDBSP1X4V2 is a 4K HDBaseT splitter with 4 HDBaseT plus 1 HDMI outputs. It distributes HDMI signal via CAT cable at 230ft (70m) with PoC, and enables IR and RS232 pass-through to control the remote displays. Build in audio de-embedder.

Reveiver unit to this model is: VLHDMIMAT4X444-R

- Integrated with HDBaseT technology, 4K@60Hz 4:4:4 supported
- 4 HDBaseT outputs with PoH at 230ft (70m)
- Analog balanced/unbalanced + digital audio output
- One HDMI output for local monitor or loop to next box
- RS232 & Bi-directional IR to control display
- Smart EDID management to avoid the display issue
- LEDs for status checking
- 4 x 3.5mm IR input jacks for connecting the four IR receivers



## **Specifications**

Features	3D	Yes
	Easy to install	Yes
	HD type	4K Ultra HD
	HDCP	Yes
	Housing material	Metal
	Maximum operating distance	70 m
	Maximum refresh rate	60 Hz
	Maximum resolution	3840 x 2160 Pixels
	Plug and Play	Yes
	Power LED	Yes
	Product colour	Black
	Rack mounting	No
Package dimensions	Gross Weight (Package, kg)	1.59 kg
Packaging content	AC adapter included	Yes
	User guide	Yes
Packaging data	Quantity per box	1 kusů
Ports & interfaces	DC-in jack	Yes
	Ethernet LAN	No
	HDMI version	1.4
	Video in	1 x HDMI
	Video out	1 x HDMI + 4x HDBaseT
	Video port type	HDMI
	Video ports quantity	5
Power	Input voltage	110 - 240 V



Power	Output voltage	24 V
Product dimensions	Net Weight (Product, kg)	0.5 kg
	Product Depth	14.8 cm
	Product Height	4.4 cm
	Product Width	22 cm
Technical details	Cascadable	Yes
	Connection to PC	Yes
	Connector type	HDMI + RJ45
	Maximum cable length	70 m
Vendor information	Brand Name	Vivolink
	Warranty	3 Year(s)
Weight & dimensions	Dimensions (WxDxH)	220mm x 148mm x 44 mm



## Other images







## **Recommended accessories**

Vivolink Receiver for VLHDMIMAT4X444



MPN: VLHDMIMAT4X444-R