

MPN: VLHDMIMAT4X444-R

Receiver for VLHDMIMAT4X444

VLHDMIMAT4X444-R HDMI 2.0 receiver which is designed to receive 4K video from transmitter at distance up to 131 feet (40 meters) and 1080P video at distances up to 230 feet (70 meters) over a single CATx cable.

It supports audio de-embedded and ARC.

It also supports bidirectional IR and RS232 pass-through to control source or display device remotely. PoC feature allows the transmitter and the receiver can be powered from each other and only one power adapter is needed in system.




- Supports HDMI 2.0 and the HDMI video resolution up to 4K@60Hz 4:4:4 HDR.
- SPDIF out on receiver for source audio de-embedding.
- Bidirectional IR, RS232 and 24V PoC.

Specifications

Features	Maximum resolution	4K@60Hz 4:4:4 8bit Pixels
Package dimensions	Gross Weight (Package, kg)	0.61 kg
Ports & interfaces	Connectivity technology	Wired
Product dimensions	Net Weight (Product, kg)	0.4 kg
Vendor information	Brand Name	Vivolink
	Warranty	3 Year(s)

Other images



Recommended accessories



**Vivolink Matrix switcher 4x4 w/4 HDMI +
4 HDBaseT out**
MPN: VLHDMIMAT4X444