

MPN: VLHDMIMAT4X444

Matrix switcher 4x4 w/4 HDMI + 4 HDBaseT out

4x4 HDBaseT matrix switcher with audio matrix.

Fully compliant with the HDMI 2.0 and HDCP 2.2.

Supports HDMI resolution up to 4K@60Hz 4:4:4, HDR10.



Features four mirrored HDMI outputs for four HDBaseT outputs, and the four HDMI outputs support 4K to 1080p down-scaling.

The four HDBaseT outputs support 24V PoC, allowing the receivers to draw their power from the matrix switcher over the HDBaseT cable.

Transmits 4K signal to the distance up to 131 feet (40 meters) and 1080p signal to the distance up to 230 feet (70 meters) over a single CATx Ethernet cable.

Supports audio matrix. Provides four digital SPDIF audio outputs and four analog L+R audio outputs for HDMI input audio de-embedding and HDBaseT output audio de-embedding. Moreover, the four digital SPDIF audio outputs supports ARC audio output from receivers.

Volume adjustment for analog L+R audio outputs.

Supports comprehensive EDID management and advanced HDCP handling.


Controllable via front panel buttons, RS232 local and pass-through, IR local and pass-through, CEC, and TCP/IP (built-in GUI).

Compatible receiver: VLHDMIMAT4X444-R

Specifications

Package dimensions	Gross Weight (Package, kg)	3.5 kg
Product dimensions	Net Weight (Product, kg)	3.4 kg
Vendor information	Brand Name	Vivolink
	Warranty	3 Year(s)

Other images



Recommended accessories



Vivolink Receiver for VLHDMIMAT4X444
MPN: VLHDMIMAT4X444-R